

INDUSTRIAL COMPONENT DATA

Eaton 9SX 8000i Power Module 9SX8KIPM 9104-22004 EATON ELECTRIC UPS On-Line 8000VA/7200W Module electronic w..

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9SX 8000i Power Module



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9SX 8000i Power Module
Catalog number	9104-22004
Category	UPS
Minimum order	1 Pcs
Document ID	EO-158512A316
Generated	2026-08-05

Product Overview

UPS On-Line 8000VA/7200W Module electronic without batteries

Eaton 9SX 8000i Power Module

Eaton 9SX Power Module, 8 kVA, 7.2 kW, Input: Hardwired, Outputs: Hardwired, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

General specifications

Product Name Eaton 9SX UPS Catalog Number 9SX8KIPM UPC 743172039385 Product Length/Depth 70 cm Product Height 44 cm Product Width 13 cm Product Weight 19 kg Compliances CE Marked

TUV

cULus Listed

CSA 22.2 Certifications IEC/EN 62040-1

UL 1778

IEC/EN 62040-2

CE

cULus Listed

EAC Battery

Runtime graph View runtime graph Battery replacement No battery Battery quantity 0 Battery management Extended battery capability Yes Electrical output

Receptacle Hardwired Voltage 230V Wattage 7.2 kW Output power factor 0.9 Output voltage range 200/208/220/230/240/250 V +/- 1% Output waveform Sine wave Output nominal voltage 230V default (200/208/220/230/240/250V) Voltage distortion output (linear load) - max 2 Feed type 1 Topology Online/Double-conversion VA rating 8 kVA Electrical input

Input connection Hardwired/fixed connection Input nominal voltage 230V default (200/208/220/230/240/250V) Nominal frequency 50/60 Hz Input power factor >.99 Input voltage range 176-276 V (100-276 V with derating) Input frequency range 40-70 Hz Communications

Includes network card No Communication USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Off

Mini-terminal block for remote power off

Dry contacts (4 outputs, relay, DB9)

Ethernet interface No User interface Multilingual graphical LCD display Potential free switch contact Yes Expansion slots One slot for optional communication card Software compatibility Eaton Intelligent Power Manager, Eaton Intelligent...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9SX 8000i Power Module with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.