

INDUSTRIAL COMPONENT DATA

PB6TUD EATON ELECTRIC Eaton Protection Box 6 Tel@ USB DIN

Brand: EATON - MOELLER | Manufacturer Part Number: PB6TUD



Manufacturer	EATON - MOELLER
MPN / Reference	PB6TUD
Catalog number	10000
Category	Multiple socket
Minimum order	1 Pcs
Document ID	EO-1F17CBE12B
Generated	2026-08-06

Product Overview

Eaton Protection Box 6 Tel@ USB DIN

Eaton 6 DIN Tel@ Protection Box, 10A, Input: Schuko, Output: (6) Schuko, Tel Line & Internet with Eaton Protection, (2) USB Charging Ports

Eaton Protection Box 6 Tel@ DIN, 10A, Input: Schuko, Output: (6) Schuko, Tel & Internet line Eaton Protection, (2) USB Charging Ports

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General Specifications

Product Name Protection Box de Eaton Catalog No. PB6TUD Ean 3553340667237 Product Length/Depth 245 mm Product Height 110 mm Product Width 47.5 mm Product Weight 0.623 kg Conformance(s) EAC

CE marked Certification(s) IEC/EN 61643-11

IEC/EN 60884-1 Model Code Eaton Protection Box 6 Tel@ USB DIN Product specifications

guy Surge Suppressor Special Features High-end surge protection device that implements 6 Schuko sockets (DIN), complies with IEC 61643-11, telephone line and internet protection, 2 USB ports, includes warranty on connected

equipment Circuit breaker Yes Core cross-section 0 mm² Halogen-free No Housing Shape Rectangular Input Connection Protective contact (SCHUKO) Internet/Phone Line Protection Yes Material quality Other NEMA Designation none Nominal Frequency 50-60 Hz Nominal Amperage 10A phase Monophasic Transient Overvoltage Current 3000 A Type of indicator Colored LEDs Number of NEMA outlets 0 Number of outputs (other) 0 Number of taps with protected contact 6 Number of

USB connections 2 Package Contents Power Cord Length 1.5 m RAL number 9003 Residual current circuit breaker No Surface Finish Mate Surface Protection Other Switchable Yes Transparent No Swivel center insert angle Other Colour White/Black Number of outputs 6 Operating Voltage 220-250 V Nominal transient overvoltage 1500 V Interruption Rating 10 AIC Operating Temperature (Max) 40 °C Operating Temperature (min.) 0 °C Mounting method Portable 35 mm DIN rail Material Plastic Equ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PB6TUD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.