

## INDUSTRIAL COMPONENT DATA

# EBAB00 EPDU BA 0U (309 16A 3P)36xC13:6xC19 EATON ELECTRIC Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 12..

Brand: EATON - MOELLER | Manufacturer Part Number: EBAB00



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | EBAB00                              |
| Catalog number  | EPDU BA 0U (309 16A 3P)36xC13:6xC19 |
| Category        | Power distribution unit (PDU)       |
| Minimum order   | 1 Pcs                               |
| Document ID     | EO-323D780086                       |
| Generated       | 2026-08-03                          |

## Product Overview

Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 12 kW, 16A, 346-415V, Outlets: (36) C13/(6) C19  
EPDU BA 0U (309 16A 3P)36XC13:6XC19

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                |
|--------------|------------------------------------------------|
| Catalog path | EATON - MOELLER > Single-phase UPS up to 11kVA |
|--------------|------------------------------------------------|

## Additional Product Information

Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 12 kW, 16A, 346-415V, Outlets: (36) C13/(6) C19  
Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 12 kW, 16A, 346-415V, Outlets: (36) C13/(6) C19  
Built-in IEC outlet eGrip retention, retains all standard IEC plugs.

60°C Operating temperature.

Colour-coded outlet and branch circuits for simple load balancing.

Hydraulic-Magnetic Circuit Breakers with accidental trip protection.

Low-profile form factor: 52 mm wide x 53 mm deep on most models.

Universal mounting system: Button mounting on rear and side + variable mounting system.

Delivery program

Type Rack PDU  
Input Connection IEC-60309 16A 3ph  
Cord Length 3m  
Input Voltage 346-415V  
Phase Three-phase  
Frequency 50/60 Hz  
Ethernet Interface No  
Serial Interface No  
Form Factor 0U (Vertical)  
Outlet Control No  
Operating Temperature 0° to 60°C (32° to 140°F)  
Outlets 36XC13 : 6XC19  
Number of Outputs C13 36  
Number of Outputs C19 6  
Amperage

Rating16AMounting DirectionVerticalETIM ClassEC002762ePDU General Prod Spec1Fitted With:Mounting materialePDU  
Other Prod SpecElectrical ConnectionConnecting cord with plugEvaluationOtherMounting Dimension (metrical)52Mounting  
Dimension (standardised)MetricSwitchableNoETIM RCBO and AFDD Product SpecsOver Voltage Category2Fuse Holders  
Prod SpecsWattage11 kW maxePDU Communication Prod SpecSNMPNoMass ConfigurationNoePDU General Prod  
SpecPackage ContentsPDU, Mounting accessories, Quickstart guide, Safety InstructionsePDU Output Prod SpecNumber  
of Outputs C200Num of Outputs PC (SCHUKO)0N...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBAB00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.