

INDUSTRIAL COMPONENT DATA

EBAB20 EPDU BA 0U (309 16A 3P)21XC13:3XC19 EATON ELECTRIC Eaton Basic Rack PDU, 0U, 24U, IEC-60309 input, 12..

Brand: EATON - MOELLER | Manufacturer Part Number: EBAB20



Manufacturer	EATON - MOELLER
MPN / Reference	EBAB20
Catalog number	EPDU BA 0U (309 16A 3P)21XC13:3XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-CFBD96D497
Generated	2026-08-04

Product Overview

Eaton Basic Rack PDU, 0U, 24U, IEC-60309 input, 12 kW, 16A, 346-415V, Outlets: (21) C13/(3) C19
EPDU BA 0U (309 16A 3P)21XC13:3XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton Basic Rack PDU, 0U, 24U, IEC-60309 input, 12 kW, 16A, 346-415V, Outlets: (21) C13/(3) C19
Eaton Basic Rack PDU, 0U, 24U, IEC-60309 input, 12 kW, 16A, 346-415V, Outlets: (21) C13/(3) C19
IEC outlet eGrip plug retention: retains all standard IEC plugs

Colour-coded outlet and branch circuits for simple load balancing

Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52mm wide x 53mm deep on most models

60 Degree C operating temperature

Installation: Button mounting on rear & side + variable mounting system

Delivery program

Type Rack PDU
Input Connection IEC-60309 16A 3ph
Cord Length 3m
Input Voltage 346-415V
Phase Three-phase
Frequency 50/60 Hz
Ethernet Interface No
Serial Interface No
Form Factor 0U (Vertical)
Outlet Control No
Operating Temperature 0° to 60°C (32° to 140°F)
Outlets 21XC13:3XC19
Number of Outputs C13 21
Number of Outputs C19 3
Amperage

Rating16AMounting DirectionVerticalETIM ClassEC002762ePDU General Prod Spec1Fitted With:Mounting materialePDU
Other Prod SpecElectrical ConnectionConnecting cord with plugEvaluationOtherMounting Dimension (metrical)52Mounting
Dimension (standardised)MetricSwitchableNoETIM RCBO and AFDD Product SpecsOver Voltage Category2Fuse Holders
Prod SpecsWattage11 kW maxePDU Communication Prod SpecSNMPNoMass ConfigurationNoePDU General Prod
SpecPackage ContentsPDU
mounting accessories
Quickstart
Safety InstructionsePDU Output Prod SpecNumber of Outputs C200Num of Outputs PC (SCHUKO)0Number of Outputs
(Other)0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBAB20 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.