

## INDUSTRIAL COMPONENT DATA

# EPDU BA 0U (C20 16A 1P)16XC13 EBAB21 EATON ELECTRIC Eaton Basic Rack PDU, 0U, 16U, C20 input, 4 kW, 16A, 200..

Brand: EATON - MOELLER | Manufacturer Part Number: EPDU BA 0U (C20 16A 1P)16XC13



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | EPDU BA 0U (C20 16A 1P)16XC13 |
| Catalog number  | EBAB21                        |
| Category        | Power distribution unit (PDU) |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-1809A1F5DF                 |
| Generated       | 2026-08-05                    |

## Product Overview

Eaton Basic Rack PDU, 0U, 16U, C20 input, 4 kW, 16A, 200-240V, Outlets: (16) C13  
EPDU BA 0U (C20 16A 1P)16XC13

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                |
|--------------|------------------------------------------------|
| Catalog path | EATON - MOELLER > Single-phase UPS up to 11kVA |
|--------------|------------------------------------------------|

## Additional Product Information

Eaton Basic Rack PDU, 0U, 16U, C20 input, 4 kW, 16A, 200-240V, Outlets: (16) C13  
Eaton Basic Rack PDU, 0U, 16U, C20 input, 4 kW, 16A, 200-240V, Outlets: (16) C13  
IEC outlet eGrip plug retention: retains all standard IEC plugs  
Colour-coded outlet and branch circuits for simple load balancing  
Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection  
Low-profile form factor: 52mm wide x 53mm deep on most models  
60 Degree C operating temperature  
Installation: Button mounting on rear & side + variable mounting system  
Delivery program  
Type Rack PDU  
Input Connection C20  
Cord Length 3m  
Input Voltage 200-240V  
Phase Single-phase  
Frequency Rating 50/60 Hz  
Ethernet Interface No  
Serial Interface No  
Form Factor 0U (Vertical)  
Outlet Control No  
Operating Temperature 0° to 60°C (32° to 140°F)  
Outlets 16XC13  
Number of Outputs C13 16  
Number of Outputs C19 0  
Amperage Rating 16A  
Mounting Direction Vertical  
ETIM Classe EC002762  
ePDU General Prod Spec 1  
Fitted With: Mounting material ePDU Other Prod Spec  
Electrical Connection Connecting cord with plug  
Evaluation Other  
Mounting Dimension (metrical) 52  
Mounting Dimension (standardised) Metric  
Switchable No  
ETIM RCBO and AFDD Product Specs  
Over Voltage Category 2  
Fuse Holders Prod

SpecsWattage3.84 kW maxePDU Communication Prod SpecSNMPNoMass ConfigurationNoePDU General Prod  
SpecPackage ContentsPDU  
mounting accessories  
Quickstart  
Safety InstructionsePDU Output Prod SpecNumber of Outputs C200Num of Outputs PC (SCHUKO)0Number of Outputs  
(Other)0Number of Outlets with Earth Pin16Fuses Holders...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EPDU BA 0U (C20 16A 1P)16XC13 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.