

INDUSTRIAL COMPONENT DATA

EBAB32 EPDU BA 0U (309 32A 3P)24XC13:6XC19 EATON ELECTRIC Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 22..

Brand: EATON - MOELLER | Manufacturer Part Number: EBAB32



Manufacturer	EATON - MOELLER
MPN / Reference	EBAB32
Catalog number	EPDU BA 0U (309 32A 3P)24XC13:6XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-065474921A
Generated	2026-08-04

Product Overview

Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 22 kW, 32A, 346-415V, Outlets: (24) C13/(6) C19
EPDU BA 0U (309 32A 3P)24XC13:6XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 22 kW, 32A, 346-415V, Outlets: (24) C13/(6) C19
Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 22 kW, 32A, 346-415V, Outlets: (24) C13/(6) C19
IEC outlet eGrip plug retention: retains all standard IEC plugs

Colour-coded outlet and branch circuits for simple load balancing

Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52mm wide x 53mm deep on most models

60 Degree C operating temperature

Installation: Button mounting on rear & side + variable mounting system

Delivery program

ePDU General Prod Spec1Fitted With:Mounting materialType Rack PDUInput ConnectionIEC-60309 32A 3PhCord

Length3mInput Voltage346-415VPhaseThree-phaseFrequency Rating50/60 HzEthernet InterfaceNoSerial InterfaceNoForm
Factor0U (Vertical)Outlet ControlNoOperating Temperature0° to 60°C (32° to 140°F)Outlets24XC13:6XC19Number of

Outputs C1324Number of Outputs C196Amperage Rating32AMounting DirectionVerticalETIM ClassEC002762ePDU Other
Prod SpecElectrical ConnectionConnecting cord with plugEvaluationOtherMounting Dimension (metrical)52Mounting
Dimension (standardised)MetricSwitchableNoETIM RCBO and AFDD Product SpecsOver Voltage Category2Fuse Holders
Prod SpecsWattage22 kW maxePDU Communication Prod SpecSNMPNoMass ConfigurationNoePDU General Prod
SpecPackage ContentsPDU
mounting accessories
Quickstart
Safety InstructionsePDU Output Prod SpecNumber of Outputs C200Num of Outputs PC (SCHUKO)0Number of Outputs
(Other)0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBAB32 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.