

INDUSTRIAL COMPONENT DATA

EBF3330W1 EATON ELECTRIC Fuse rail, low voltage, 160 A, AC 690 V, NH00, 3P, IEC, 100mm busbar, bridge termin..

Brand: EATON - MOELLER | Manufacturer Part Number: EBF3330W1



Manufacturer	EATON - MOELLER
MPN / Reference	EBF3330W1
Catalog number	10000
Category	In-line fuse base
Minimum order	1 Pcs
Document ID	EO-01238B6DF4
Generated	2026-08-06

Product Overview

SIZE3>185MM BUS>VER RAIL>WITH 2V-CLAMPS

SIZE3>185MM BUS>VER RAIL>WITH 2V-CLAMPS

Eaton Bussmann series low voltage NH fuse base, Fuse rail, low voltage, 630 A, AC 690 V, NH3, 3P, IEC, 185 mm busbar, 2-V Terminals with double V-clamps

Fuse accessory, Fuse rail, low voltage, 630 A, AC 690 V, NH3, 3P, IEC, vertical, 185 mm busbar mounting, double V-clamps, NH3 fuse-links, IEC 60269-1, IP20 (with fuse-link shrouds)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage NH fuse base Catalog Number EBF3330W1 EAN 5027590336574

Product Length/Depth 715 mm Product Height 190 mm Product Width 103 mm Product Weight 4051 g Compliances CE

Certifications IEC 60269-1

IEC 60269-2 Electrical rating

Amperage Rating 630 A Voltage rating 690 Product specifications

Number of poles Three-pole Mounting method Busbar

ETIM for EBF3330W1 Low-voltage industrial controls and switchgear (EC001046)

Feature Name

Feature Value

Model (EF000010)
Fuse base
Double interrupting (EF007103)
No
Rated permanent current I_u (EF001389)
630 A
Distance between rail centre, 40 mm (EF001431)
No
Distance between rail centre, 50 mm (EF001430)
No
Distance between rail centre, 60 mm (EF001432)
No
Distance between rail centre, 100 mm (EF006048)
No
Distance between rail centre, 185 mm (EF006049)
Yes
Max. rated operation voltage U_e AC (EF007355)
690 V
Conditioned rated short-circuit current I_q (EF001444)
0.1 kA
Type of electrical connection of main circuit (EF006819)
Cable clamp
Number of poles (EF001391)
3
Construction size fuse insert (EF001452)
NH3
Release indication (EF011943)
None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBF3330W1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.