

INDUSTRIAL COMPONENT DATA

EBH00O3TM8L EATON ELECTRIC Switch disconnecter, low voltage, 160 A, AC 690 V, NH000, AC21B, 3P, IEC, plate m..

Brand: EATON - MOELLER | Manufacturer Part Number: EBH00O3TM8L



Manufacturer	EATON - MOELLER
MPN / Reference	EBH00O3TM8L
Catalog number	10000
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-0A09BA398A
Generated	2026-08-06

Product Overview

SIZE 00 HOR FSD, MOUNT PLATE: M8 SCREWS

Eaton Busmann series low voltage NH fuse base, Switch disconnecter, low voltage, 160 A, AC 690 V, NH00, AC23B, 3P, IEC, panel mounting, for connection of conductors with lug terminals, lenghtened terminal shrouds

Fuse accessory, Switch disconnecter, low voltage, 160 A, AC 690 V, NH00, AC23B, 3P, IEC, Horizontal, mounting plate type, M8 screws, lenghtened terminal shrouds, NH00 fuse-links, IEC 60947-1, IEC 60947-3, IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Busmann Series Low Voltage fuses and accessories**

Additional Product Information

General specifications

Product Name Eaton Busmann series low voltage NH fuse base Catalog Number EBH00O3TM8L EAN 5027590409131

Product Length/Depth 110 mm Product Height 200 mm Product Width 95 mm Product Weight 687 g Compliances CE

Certifications IEC/EN 60947-1

IEC 60947-3 Electrical rating

Amperage Rating 160 A Voltage rating 690 Product specifications

Number of poles Three-pole Mounting method DIN rail

60 mm busbar mounting

ETIM for EBH00O3TM8L Low-voltage industrial controls and switchgear (EC001040)

Feature Name

Feature Value

Version as main switch (EF006981)
No
Version as safety switch (EF006985)
No
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated permanent current I_u (EF001389)
160 A
Rated operation power at AC-23, 400 V (EF007027)
0.064 kW
Conditioned rated short-circuit current I_q (EF001444)
0.08 kA
Suitable for fuses (EF006692)
NH00
Number of poles (EF001391)
3
With error protection (EF007384)
No
Type of electrical connection of main circuit (EF006819)
Screw connection
Cable entry (EF000537)
Other
Equipped with connectors (EF011696)
No
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for busbar mounting (EF007259)
No
Type of control element (EF006976)
Cover grip
Position control element (EF009410)
Front
Motor drive optional (EF007386)
No
Motor drive integrated (EF006697)
No
Version as emergency stop installation (EF006959)
No
Degree of protection (IP), front side (EF003118)
IP30

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBH00O3TM8L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.