

INDUSTRIAL COMPONENT DATA

EBH313TM2 EATON ELECTRIC Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC22B, 3P, IEC, 60mm busbar..

Brand: EATON - MOELLER | Manufacturer Part Number: EBH313TM2



Manufacturer	EATON - MOELLER
MPN / Reference	EBH313TM2
Catalog number	10000
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5444FBB1F0
Generated	2026-08-06

Product Overview

Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC22B, 3P, IEC, 60mm busbar, top/bottom cable terminals, M12 screws

disconnecter, BT, 630 A, AC 690 V, NH3, AC22B, 3P, IEC

Fuse accessory, Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC22B, 3P, IEC, Horizontal, 60 mm busbar mounting, top/bottom cable terminals, M12 screws, NH3 fuse-links, IEC 60947-1, IEC 60947-3, IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann fuses

Additional Product Information

Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC22B, 3P, IEC, 60mm busbar, top/bottom cable terminals, M12 screws Fuse accessory, Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC22B, 3P, IEC, Horizontal, 60 mm busbar mounting, top/bottom cable terminals, M12 screws, NH3 fuse-links, IEC 60947-1, IEC 60947-3, IP20 Delivery program

Product range Fuse accessory Basic function Switch disconnecter Field of application low voltage Rated current [I] 630 A Rated voltage AC 690 V Construction size NH3 Utilization category AC22B Description 60 mm busbar mounting top/bottom cable terminals

M12 screws Protection IP20 Number of poles 3P usable for size/applications NH3 fuse-links Standard/Approval IEC Shape Horizontal Standards/Regulations IEC 60947-1

IEC 60947-3 Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040) Electric engineering, automation,

process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector ( [AKF058013]) Version as main switch No Version as safety switch No Max. rated operation voltage Ue AC 690 V Rated permanent current Iu 630 A Rated operation power at AC-23, 400 V 252 kW Conditioned rated short-circuit current Iq 25 kA Rated short-time withstand current Icw 25 kA Suitable for fuses NH3 Number of poles 3 With error protection No Type of electrical connection of main circuit Screw connection Cable entry....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBH313TM2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.