

INDUSTRIAL COMPONENT DATA

EBV0033TS8 EATON ELECTRIC Switch disconnecter, low voltage, 160 A, AC 690 V, NH000, AC21B, 3P, IEC, plate mo..

Brand: EATON - MOELLER | Manufacturer Part Number: EBV0033TS8



Manufacturer	EATON - MOELLER
MPN / Reference	EBV0033TS8
Catalog number	10000
Category	In-line fuse base
Minimum order	1 Pcs
Document ID	EO-7514808229
Generated	2026-08-06

Product Overview

SIZE00185MM VER FSD BRIDGE TER WITH BRI

Eaton Bussmann series low voltage NH fuse base, Switch disconnecter, low voltage, 160 A, AC 690 V, NH00, AC22B, 3P, IEC, 185 mm busbar, simultaneous switching, screw terminals with M8 Screws

Fuse accessory, Switch disconnecter, low voltage, 160 A, AC 690 V, NH00, AC22B, 3P, IEC, vertical, 185 mm busbar mounting, 3-phase simultaneous switching, S-bridge clamps, M8 screws, NH00 fuse-links, IEC 60947-1, IEC 60947-3, IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage NH fuse base Catalog Number EBV0033TS8 EAN 5027590336291

Product Length/Depth 135 mm Product Height 715 mm Product Width 55 mm Product Weight 2598 g Compliances CE

Certifications IEC/EN 60947-1

IEC 60947-3 Electrical rating

Voltage rating 690 Product specifications

Number of poles Three-pole Mounting method Busbar

ETIM for EBV0033TS8 Low-voltage industrial controls and switchgear (EC001046)

Feature Name

Feature Value

Model (EF000010)

Fuse switch disconnecter
Double interrupting (EF007103)
false
Rated permanent current I_u (EF001389)
160 A
Distance between rail centre, 40 mm (EF001431)
false
Distance between rail centre, 50 mm (EF001430)
false
Distance between rail centre, 60 mm (EF001432)
false
Distance between rail centre, 100 mm (EF006048)
false
Distance between rail centre, 185 mm (EF006049)
true
Max. rated operation voltage U_e AC (EF007355)
690 V
Conditioned rated short-circuit current I_q (EF001444)
0.08 kA
Type of electrical connection of main circuit (EF006819)
Other
Number of poles (EF001391)
3
Construction size fuse insert (EF001452)
NH00
Release indication (EF011943)
None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBV0033TS8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.