

INDUSTRIAL COMPONENT DATA

EBV233SV1 EATON ELECTRIC Switch disconnecter, low voltage, 400 A, AC 690 V, NH1/NH2, AC22B, 3P, IEC, 185 mm ..

Brand: EATON - MOELLER | Manufacturer Part Number: EBV233SV1



Manufacturer	EATON - MOELLER
MPN / Reference	EBV233SV1
Catalog number	10000
Category	In-line fuse base
Minimum order	1 Pcs
Document ID	EO-B8E8BB10C8
Generated	2026-08-06

Product Overview

SIZE1&2 185MM VER FSD V-TER WITH V-CLAMP

Eaton Busmann series low voltage NH fuse base, Switch disconnecter, low voltage, 400 A, AC 690 V, NH1 NH2, AC22B, 3P, IEC, 185 mm busbar, each phase switching, V-terminals with V-clamps

Fuse accessory, Switch disconnecter, low voltage, 400 A, AC 690 V, NH1, NH2, AC22B, 3P, IEC, vertical, 185 mm busbar mounting, single phase switching, V-clamps, NH1 and NH2 fuse-links, IEC 60947-1, IEC 60947-3, IP30

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Busmann series low voltage NH fuse base Catalog Number EBV233SV1 EAN 5027590335607

Product Length/Depth 195 mm Product Height 675 mm Product Width 110 mm Product Weight 5536 g Compliances CE

Certifications IEC/EN 60947-1

IEC 60947-3 Electrical rating

Voltage rating 690 Product specifications

Number of poles Three-pole Mounting method Busbar

ETIM for EBV233SV1 Low-voltage industrial controls and switchgear (EC001046)

Feature Name

Feature Value

Model (EF000010)

Fuse switch disconnecter
Double interrupting (EF007103)
No
Rated permanent current I_u (EF001389)
400 A
Distance between rail centre, 40 mm (EF001431)
No
Distance between rail centre, 50 mm (EF001430)
No
Distance between rail centre, 60 mm (EF001432)
No
Distance between rail centre, 100 mm (EF006048)
No
Distance between rail centre, 185 mm (EF006049)
Yes
Max. rated operation voltage U_e AC (EF007355)
690 V
Conditioned rated short-circuit current I_q (EF001444)
0.1 kA
Type of electrical connection of main circuit (EF006819)
Cable clamp
Number of poles (EF001391)
3
Construction size fuse insert (EF001452)
NH1, NH2
Release indication (EF011943)
None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBV233SV1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.