

**INDUSTRIAL COMPONENT DATA**

# EBV333SM2 EATON ELECTRIC Fuse rail, low voltage, 630 A, AC 690 V, NH3, 3P, IEC, 185 mm busbar, screw termina..

Brand: EATON - MOELLER | Manufacturer Part Number: EBV333SM2



|                 |                   |
|-----------------|-------------------|
| Manufacturer    | EATON - MOELLER   |
| MPN / Reference | EBV333SM2         |
| Catalog number  | 10000             |
| Category        | In-line fuse base |
| Minimum order   | 1 Pcs             |
| Document ID     | EO-40F6B6161A     |
| Generated       | 2026-08-06        |

## Product Overview

SIZE3>185MM SCREW TERM WITH PRESSED NUTS

Eaton Bussmann series low voltage NH fuse base, Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC21B, 3P, IEC, 185 mm busbar, single phase switching, screw terminals with pressed nuts M12

Fuse accessory, Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC21B, 3P, IEC, vertical, 185 mm busbar mounting, single phase switching, M12 screws with pressed nuts, NH3 fuse-links, IEC 60947-1, IEC 60947-3, IP30

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      EATON - MOELLER &gt; Bussmann Series Low Voltage fuses and accessories

## Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage NH fuse base Catalog Number EBV333SM2 EAN 5027590336079

Product Length/Depth 195 mm Product Height 675 mm Product Width 110 mm Product Weight 6234 g Compliances CE

Certifications IEC/EN 60947-1

IEC 60947-3 Electrical rating

Voltage rating 690 Product specifications

Number of poles Three-pole Mounting method Busbar

ETIM for EBV333SM2 Low-voltage industrial controls and switchgear (EC001046)

Feature Name

Feature Value

Model (EF000010)

Fuse switch disconnecter  
Double interrupting (EF007103)  
No  
Rated permanent current I<sub>u</sub> (EF001389)  
630 A  
Distance between rail centre, 40 mm (EF001431)  
No  
Distance between rail centre, 50 mm (EF001430)  
No  
Distance between rail centre, 60 mm (EF001432)  
No  
Distance between rail centre, 100 mm (EF006048)  
No  
Distance between rail centre, 185 mm (EF006049)  
Yes  
Max. rated operation voltage U<sub>e</sub> AC (EF007355)  
690 V  
Conditioned rated short-circuit current I<sub>q</sub> (EF001444)  
0.08 kA  
Type of electrical connection of main circuit (EF006819)  
Screw connection  
Number of poles (EF001391)  
3  
Construction size fuse insert (EF001452)  
NH3  
Release indication (EF011943)  
None

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBV333SM2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.