

## INDUSTRIAL COMPONENT DATA

**EBV333TV0 EATON ELECTRIC Switch disconnecter, low voltage, 160 A, AC 690 V, NH00, AC22B, 3P, IEC, 100 mm bus..**

Brand: EATON - MOELLER | Manufacturer Part Number: EBV333TV0



|                 |                   |
|-----------------|-------------------|
| Manufacturer    | EATON - MOELLER   |
| MPN / Reference | EBV333TV0         |
| Catalog number  | 10000             |
| Category        | In-line fuse base |
| Minimum order   | 1 Pcs             |
| Document ID     | EO-D70201F0A2     |
| Generated       | 2026-08-06        |

**Product Overview**

SIZE3&gt;185MM BUS&gt;V-TER WITHOUT V-CLAMPS

SIZE3&gt;185MM BUS&gt;V-TER WITHOUT V-CLAMPS

Eaton Bussmann series low voltage NH fuse base, Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC21B, 3P, IEC, 185 mm busbar, simultaneous switching, V-terminals without V-clamps

Fuse accessory, Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC21B, 3P, IEC, vertical, 185 mm busbar mounting, 3-phase simultaneous switching, V-terminals without V-clamps, NH3 fuse-links, IEC 60947-1, IEC 60947-3, IP30

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                                     |
|--------------|---------------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories |
|--------------|---------------------------------------------------------------------|

**Additional Product Information**

## General specifications

Product Name Eaton Bussmann series low voltage NH fuse base Catalog Number EBV333TV0 EAN 5027590540742

Product Length/Depth 195 mm Product Height 675 mm Product Width 110 mm Product Weight 6032 g Compliances CE

Certifications IEC/EN 60947-1

IEC 60947-3 Product specifications

Type Fuse accessory Application Transformer substations, industrial low voltage distribution boards, cable cabinets Rated permanent current (Iu) 630 A Conditioned rated short-circuit current Iq 0.08 kA Double interrupting No Number of poles Three-pole Construction size (fuse inserts) NH3 Distance Between rail center: 185 mm Electrical connection type of main circuit Other Construction size NH3 Fuse shape Vertical Release indication None Suitable for NH3 Suitable for fuses NH3 Mounting method Busbar Voltage rating 690 Electrical connection type Other Model Fuse switch disconnecter Rated

operating voltage (Ue) at AC - max 690 V

ETIM for EBV333TV0 Low-voltage industrial controls and switchgear (EC001046)

Feature Name

Feature Value

Model (EF000010)

Fuse switch disconnecter

Double interrupting (EF007103)

No

Rated permanent current Iu (EF001389)

630 A

Distance between rail centre, 40 mm (EF001431)

No

Distance between rail centre, 50 mm (EF001430)

No

Distance between rail centre, 60 mm (EF001432)

No

Distance between rail centre, 100 mm (EF006048)

No

Distance between rail centre, 185 mm (EF006049)

Yes

Max. rated operation voltage Ue AC (EF007355)

690 V

Conditioned rated short-circuit curre...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EBV333TV0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.