

INDUSTRIAL COMPONENT DATA

XNE-GWBR-2ETH-IP 140047 Y7-140047 EATON ELECTRIC ECO gateway for XI/ON I/O system, ethernet IP

Brand: EATON - MOELLER | Manufacturer Part Number: XNE-GWBR-2ETH-IP



Manufacturer	EATON - MOELLER
MPN / Reference	XNE-GWBR-2ETH-IP
Catalog number	Y7-140047
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-848CE19EED
Generated	2026-08-05

Product Overview

ECO gateway for XI/ON I/O system, ethernet IP

XNE-GWBR-2ETH-IP

Eaton XNE ECO gateway for XI/ON I/O system, ethernet IP

The XI/ON standard I/O system adds cost and space-optimized I/O modules and gateways to the XI/ON I/O system. The ECO modules do not need base modules and are fully compatible with the standard XI/ON system. High channel density (up to 16 DI/DO on 13 mm), push-in spring-cage terminals, 8 or 16 channels per module. The ECO gateways support the CANopen bus systems Profibus DP and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

General specifications

Product Name Eaton XNE Gateway Catalog Number 140047 Model Code XNE-GWBR-2ETH-IP EAN 7640130095281

Product Length/Depth 129 mm Product Height 75 mm Product Width 33.5 mm Product Weight 0.136 kg Certifications

IEC/EN 61131-2

IEC/EN 61000-6-2

CULus

IEC/EN 61000-6-4

Rated data for terminations according to IEC/EN 60947-7-1

CE Features & Functions

Features Fieldbus connection over separate bus coupler possible Fitted with: Bus refreshing module

Potential separation General

Accessories 1 x end plate XN-ABPL and 2 x end bracket XN-WEW-32/2-SW included with supplied equipment. Admissible range 18 - 30 V DC, Networking Configuration Maximum station configuration: 74 cards (XN, XNE) of slice design or max. length of station: 1 m Degree of protection IP20 Mounting method Rail mounting possible Residual ripple According to EN 61131-2 Type Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Mechanical, According to IEC/EN 60068-2-27

Continuous according to IEC/EN 60068-2-29 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -25 °C Ambient storage temperature - max 85 °C Environmental conditions Harmful gasses - SO₂: 10 ppm (relative humidity < 75%, no condensation)

Harmful gasses - H₂S: 1 ppm (relative humidity < 75%, no c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XNE-GWBR-2ETH-IP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.