

INDUSTRIAL COMPONENT DATA

EPDU IL 0U (309 32A 1P)1x309 EILB14 EATON ELECTRIC

Eaton In-line Metered Rack PDU, 0U, 10U, Input IEC-60309 ..

Brand: EATON - MOELLER | Manufacturer Part Number: EPDU IL 0U (309 32A 1P)1x309



Manufacturer	EATON - MOELLER
MPN / Reference	EPDU IL 0U (309 32A 1P)1x309
Catalog number	EILB14
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-729BAA06B0
Generated	2026-08-05

Product Overview

Eaton In-line Metered Rack PDU, 0U, 10U, Input IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 1XIEC60309 32A

EPDU IL 0U (309 32A 1P)1X309

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton In-line Metered Rack PDU, 0U, 10U, Input IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 1XIEC60309 32A
Eaton In-line Metered Rack PDU, 0U, 10U, Input IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 1XIEC60309 32A

Input and Phase Metering

Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit

Low-profile form factor: 52mm wide x 53mm deep on most models

60 Degree C operating temperature

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Optional Temp/Humidity sensor

En masse configuration and update available via Intelligent Power Manager software

Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software

Trigger advanced actions including Vmware SRM and VM migration via via Intelligent Power Manager software

Installation: Button mounting on rear & side, variable mounting system, horizontal mounting system

Delivery program

TypeRack PDUInput ConnectionIEC-60309 32A 1PhCord Length3mInput Voltage200-240VPhaseSingle-phaseFrequency
Rating50/60 HzEthernet InterfaceYesSerial InterfaceYesForm Factor0U (Vertical)Outlet ControlNoOperating Temperature0°
to 60°C (32° to 140°F)Outlets1XIEC60309 32ANumber of Outputs C130Number of Outputs C190Amperage
Rating32AMounting DirectionVerticalETIM ClassEC002762ePDU General Prod Spec1Fitted With:Display
Ampere Meter
Mounting materialePDU Other Prod SpecElectrical ConnectionConnecting cord with plugEvaluationAt distanceMoun...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EPDU IL 0U (309 32A 1P)1x309 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.