

INDUSTRIAL COMPONENT DATA

EPDU IL 0U (2X309 32A 1P)2X309 EILB25 EATON ELECTRIC

Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-..

Brand: EATON - MOELLER | Manufacturer Part Number: EPDU IL 0U (2X309 32A 1P)2X309



Manufacturer	EATON - MOELLER
MPN / Reference	EPDU IL 0U (2X309 32A 1P)2X309
Catalog number	EILB25
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-E4657D8FC7
Generated	2026-08-03

Product Overview

Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 2XIEC60309 32A
EPDU IL 0U (2X309 32A 1P)309 32A 1PX2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 2XIEC60309 32A
Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 2XIEC60309 32A
Input and Phase Metering
Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit
Low-profile form factor: 52mm wide x 53mm deep on most models
60 Degree C operating temperature
HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
Optional Temp/Humidity sensor
En masse configuration and update available via Intelligent Power Manager software
Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software
Trigger advanced actions including Vmware SRM and VM migration via via Intelligent Power Manager software
Installation: Button mounting on rear & side, variable mounting system, horizontal mounting system
Delivery program

TypeRack PDUInput Connection2 x IEC-60309 32A 1PhCord Length3mInput
Voltage200-240VPhaseSingle-phaseFrequency Rating50/60 HzEthernet InterfaceYesSerial InterfaceYesForm Factor0U
(Vertical)Outlet ControlNoOperating Temperature0° to 60°C (32° to 140°F)Outlets2XIEC60309 32ANumber of Outputs
C130Number of Outputs C190Amperage Rating32AMounting DirectionVerticalETIM ClassEC002762ePDU General Prod
Spec1Fitted With:Ampere Meter
Mounting material
DisplayePDU Other Prod SpecElectrical ConnectionConnecting cord with plugEvaluationAt....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EPDU IL 0U (2X309 32A 1P)2X309 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.