

INDUSTRIAL COMPONENT DATA

EPDU IL 0U (2X309 32A 3P)2X309 EILB26 EATON ELECTRIC

Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-..

Brand: EATON - MOELLER | Manufacturer Part Number: EPDU IL 0U (2X309 32A 3P)2X309



Manufacturer	EATON - MOELLER
MPN / Reference	EPDU IL 0U (2X309 32A 3P)2X309
Catalog number	EILB26
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-D0DDAB7DA9
Generated	2026-08-03

Product Overview

Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 2XIEC60309 32A 3P

EPDU IL 0U (2X309 32A 3P)309 32A 3PX2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 2XIEC60309 32A 3P
Eaton In-line Metered Rack PDU, 0U, 10U, Input 2 x IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 2XIEC60309 32A 3P
Phase Metering, Circuit Breaker Current Metering and Input Metering.

Hot-Swap Control module with advanced LCD.

Optional Temperature/Humidity sensor.

Daisy-Chain up to 8 ePDUs, reduce network infrastructure costs.

Power chain monitoring & Real time Intelligence on your Data Center, via Eaton Intelligent Power Manager Infrastructure.

Trigger advanced actions including VMware SRM and VM migration via Intelligent Power Manager IT software.

60°C Operating temperature.

Low-profile form factor: 52 mm wide x 53 mm deep on most models.

Mass configuration and update available via Intelligent Power Manager IT software.

Delivery program

Type Rack PDU Input Connection 2 x IEC-60309 32A 3Ph Cord Length 3m Input

Voltage346-415VPhaseThree-phaseFrequency Rating50/60 HzEthernet InterfaceYesSerial InterfaceYesForm Factor0U
(Vertical)Outlet ControlNoOperating Temperature0° to 60°C (32° to 140°F)Outlets2XIEC60309 32A 3PNumber of Outputs
C130Number of Outputs C190Amperage Rating32AMounting DirectionVerticalETIM ClassEC002762ePDU General Prod
Spec1Fitted With:Display
Mounting material
Ampere MeterePDU Other Prod SpecElectrical ConnectionConnecting cord with plugEvaluationAt distanceMounting
Dimension (metrical)52Mounting Dimension (standardised)MetricSwitchableNoET...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EPDU IL 0U (2X309 32A 3P)2X309 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.