

INDUSTRIAL COMPONENT DATA

Eaton Ellipse PRO 650 IEC ELP650IEC 9207-43390 EATON ELECTRIC Eaton Ellipse PRO 650 IEC

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton Ellipse PRO 650 IEC



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton Ellipse PRO 650 IEC
Catalog number	9207-43390
Category	UPS
Minimum order	1 Pcs
Document ID	EO-559E52B479
Generated	2026-08-06

Product Overview

Eaton Ellipse PRO 650 IEC

Eaton Ellipse PRO UPS IEC, 650 VA, 400 W, Input: C14, Outputs: (3) C13, (1) C13 surge only, Tower

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton Ellipse PRO UPS Catalog Number ELP650IEC UPC 743172437334 Product Length/Depth 82 mm

Product Height 260 mm Product Width 285 mm Product Weight 6.6 kg Warranty 3 year Compliances CE Marked

Certifications IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC Battery

Battery type Sealed, lead-acid Runtime graph Battery replacement User replaceable Battery quantity 1 Battery management Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable Battery rating 12 V / 7 Ah Extended battery capability No Electrical output

Receptacle (3) C13, (1) C13 surge only Voltage 230V Wattage 400W Output power factor 0.6 Output voltage range 176-284 V Output nominal voltage 230V default (220/230/240V) Feed type 1 Topology Line-interactive VA rating 650 VA Electrical input

Input connection C14 Input nominal voltage 230V default (220/230/240V) Nominal frequency 50/60 Hz Input voltage range

165-285 V (adjustable to 150-285 V) Input frequency range 46-70 Hz Communications

Includes network card No Communication USB port (HID compliant) Ethernet interface No User interface LCD (UPS status and measurements, configuration of UPS settings) Potential free switch contact No Expansion slots No Software compatibility Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings) Type of interface USB Environmental

Altitude 2000 m Noise level

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton Ellipse PRO 650 IEC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.