

INDUSTRIAL COMPONENT DATA

EMAB04 EPDU MA 0U (309 16A 1P)20XC13:4XC19 EATON ELECTRIC EMAB04 EPDU MA 0U (309 16A 1P)20XC13:4XC19

Brand: EATON - MOELLER | Manufacturer Part Number: EMAB04



Manufacturer	EATON - MOELLER
MPN / Reference	EMAB04
Catalog number	EPDU MA 0U (309 16A 1P)20XC13:4XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-7111F4881B
Generated	2026-08-05

Product Overview

EMAB04 EPDU MA 0U (309 16A 1P)20XC13:4XC19

Eaton Managed Rack PDU, 0U, 36U, Input IEC-60309 16A 1Ph, 3.7 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

EPDU MA 0U (309 16A 1P)20XC13:4XC19 Eaton Managed Rack PDU, 0U, 36U, Input IEC-60309 16A 1Ph, 3.7 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19 Remote Site Management.

Turn off unused outlets to control commissioning.

Phase Metering, Circuit Breaker Current Metering and Input Metering.

Circuit Breaker Status Monitoring.

Level 3 PUE measurements.

Outlet and IT Equipment Switching/reboot /sequencing across A and B feed in Daisy-Chain.

Sequence Outlets to avoid in-rush current, to ensure equipment starts in correct order.

Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit.

Hot-Swap Control module with advanced LCD.

Optional Temperature/Humidity sensor.

Built-in IEC outlet eGrip retention, retains all standard IEC plugs.

[Delivery program

Power Distribution Prod Spec Type Rack PDU ePDU Other Prod Spec Electrical Connection Connecting cord with plug

Evaluation At distance Mounting Dimension (metrical) 52 Mounting Dimension (standardised) Metric Ampere Meter Yes Switchable Yes Over Voltage Category 2 ePDU Input Prod Spec Input Connection IEC-60309 16A 1Ph Cord Length 3m Wattage 3.84 kW max Input Voltage 200-240V Phase Single-phase Frequency Rating 50/60 Hz ePDU Communication Prod Spec With Temperature Measurement No Communication HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS SNMP Yes Ethernet Interface Yes Display Yes LED Indicator No Serial Interface Yes Mass Configuration Yes ePDU General Prod Spec Form Fact...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMAB04 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.