

INDUSTRIAL COMPONENT DATA

**EMAB71 EPDU MA 0U (309 32A 1P)28XC13:4XC19 EATON
ELECTRIC EPDU MA 0U (309 32A 1P)28XC13:4XC19**

Brand: EATON - MOELLER | Manufacturer Part Number: EMAB71



Manufacturer	EATON - MOELLER
MPN / Reference	EMAB71
Catalog number	EPDU MA 0U (309 32A 1P)28XC13:4XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-AB7A3EA018
Generated	2026-08-05

Product Overview

EPDU MA 0U (309 32A 1P)28XC13:4XC19

EMAB71 - EPDU MA 0U (309 32A 1P)28XC13:4XC19

Eaton Managed Rack PDU, 0U, 42U, Input IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 28XC13:4XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

EPDU MA 0U (309 32A 1P)28XC13:4XC19 Eaton Managed Rack PDU, 0U, 42U, Input IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 28XC13:4XC19 Securely allows remote control and remote rebooting

Allows device level metering over A and B feeds

Input and Phase Metering, Circuit Breaker Current Metering, circuit Breaker status monitoring

Level 3 PUE measurements

Switch and Meter Equipment on/off across both A and B feed (Requires Daisy Chained ePDUs)

Sequence Outlets to avoid in-rush current, to ensure equipment starts in correct order

Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit

IEC outlet eGrip plug retention: retains all standard IEC plugs

60 Degree C operating temperature

Colour-coded outlet and branch circuits for simple load balancing

Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52mm wide x 53mm deep on most models

En masse configuration and update available via Intelligent Power Manager software

Installation: Button mounting on rear & side + variable mounting system

Delivery program

Type Rack PDU Input Connection IEC-60309 32A 1Ph Cord Length 3m Input Voltage 200-240V Phase Single-phase Frequency
Rating 50/60 Hz Ethernet Interface Yes Serial Interface Yes Form Factor 0U (Vertical) Outlet Control Yes Operating
Temperature 0° to 60°C (32° to 140°F) Outlets 28XC13:4XC19 Number of Outputs C13 28 Number of Outputs C19 4 Amperage
Rating 32A Mounting Direction Vertical ETIM Class EC002762e PDU General Prod...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMAB71 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.