

INDUSTRIAL COMPONENT DATA

EME3P63BMODBUSMID 167410 EATON ELECTRIC Power meter, 3 N, 63 A, MODBUS, MID

Brand: EATON - MOELLER | Manufacturer Part Number: EME3P63BMODBUSMID



Manufacturer	EATON - MOELLER
MPN / Reference	EME3P63BMODBUSMID
Catalog number	167410
Category	Kilowatt-hour meter
Minimum order	1 Pcs
Document ID	EO-C8FBB034DB
Generated	2026-08-03

Product Overview

Power meter, 3 N, 63 A, MODBUS, MID

63A MODB MID Energy Meter

Digital real power meter with partial real power meter that can be set to zero and featuring integrated Modbus RTU communication - 2 tariffs, real power meter with real power partial meter for direct connection 0.25-5 (63) A, and integrated Modbus RTU communications - 2 tariffs, for direct connection up to 63 A, display with 9 numbers for showing 8 power registers, wrong connection signal (phase mix-up and phase failure), accuracy class 1 for real power and power as per EN 50470-3 (B), perfect operating current range (Ist ... I_{max}), for direct connection 63 A = 0.015 ... 63 A, power register can be set to zero (not on MID type), "Partial" power register can be set to zero in MID type as well, sealable terminal covers, power register for input and output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Power meter, 3 N, 63 A, MODBUS, MID Eaton Catalog No. EME3P63BMODBUSMID Digital real power meter with partial real power meter that can be set to zero and featuring integrated Modbus RTU communication - 2 tariffs, real power meter with real power partial meter for direct connection 0.25-5 (63) A, and integrated Modbus RTU communications - 2 tariffs, for direct connection up to 63 A, display with 9 numbers for showing 8 power registers, wrong connection signal (phase mix-up and phase failure), accuracy class 1 for real power and power as per EN 50470-3 (B), perfect operating current range (Ist ... I_{max}), for direct connection 63 A = 0.015 ... 63 A, power register can be set to zero (not on MID type), "Partial" power register can be set to zero in MID type as well, sealable terminal covers, power register for input and output [Technical data

ETIM 7.0

Meters (EG000045) / Kilowatt-hour meter (EC001506) Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Electronic electricity meter ( [AFZ828014]) Type of meter Electromechanical Nominal current (In) 80 A Max. current (Imax) 80 A Nominal voltage (Un) N-L 184 - 276 V Nominal voltage (Un) L-L 319 - 480 V Frequency 50 - 50 Hz Accuracy class B Pole type Three conductor Model Direct measurement Energy type Effective power Suitable for Purchase/supply Tariff type Two-tariff Tariff control Internal Measurin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EME3P63BMODBUSMID with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.