

INDUSTRIAL COMPONENT DATA

Q25LPV-S 257064 EATON ELECTRIC

Emergency-stop/emergency stop illuminated pushbutton, black, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q25LPV-S



Manufacturer	EATON - MOELLER
MPN / Reference	Q25LPV-S
Catalog number	257064
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-93FFE41872
Generated	2026-08-05

Product Overview

Emergency-stop/emergency stop illuminated pushbutton, black, maintained

Q25LPV-S

HALT/STOP-Button, Product range: RMQ16, Single unit, Design: Mushroom-shaped, Diameter: 28 mm, Illumination: Illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850, EN 418, Pushbutton remains in pushed position, Color Mushroom head: Black, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 × 25 mm, Information about equipment supplied: with built-in multiple LED, 24 V DC, I_e = 15 mA, Positive pole at X1, No bulb replacement required.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Emergency-stop/emergency stop illuminated pushbutton, black, maintained HALT/STOP-Button, Product range: RMQ16, Single unit, Design: Mushroom-shaped, Diameter: 28 mm, Illumination: Illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850, EN 418, Pushbutton remains in pushed position, Colour Mushroom head: Black, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 × 25 mm, Information about equipment supplied: with built-in multiple LED, 24 V DC, I_e = 15 mA, Positive pole at X1, No bulb replacement required. Delivery program

Product range RMQ16 Basic function STOP pushbuttons

Emergency stop pushbuttons Mounting hole diameter [?] 16 mm Single unit/Complete unit Single unit Design Mushroom-shaped Diameter [?] 28 mm Illumination Illuminated Approval Pull-to-release function Description Tamper-proof according to ISO 13850, EN 418 Pushbutton remains in pushed position Colour Mushroom head Black Degree of Protection IP65 Connection to SmartWire-DT no Information about equipment supplied with built-in multiple LED, 24 V DC, I_e = 15 mA Positive pole at X1 No bulb replacement required. Design verification as per IEC/EN 61439 Technical data for design verification Rated operational current for specified heat dissipation [I_n] 0 A Heat dissipation per pole, current-dependent [P_{vid}] 0 W Equipment heat dissipation, current-dependent [P_{vid}] 0 W Static heat dissipation, non-current-dependent [P_{vs}] 0.36 W Heat dissipation capacity [P_{diss}] 0 W Operating ambient temperature...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25LPV-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.