

INDUSTRIAL COMPONENT DATA

Q25PV-S 257063 Y7-257063 EATON ELECTRIC

Emergency-stop/emergency stop pushbutton, black, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q25PV-S



Manufacturer	EATON - MOELLER
MPN / Reference	Q25PV-S
Catalog number	Y7-257063
Category	Front element for mushroom push-button
Minimum order	5 Pcs
Document ID	EO-8588D28389
Generated	2026-08-04

Product Overview

Emergency-stop/emergency stop pushbutton, black, maintained

Q25PV-S

Eaton Moeller® series RMQ16 Emergency-stop/emergency switching off pushbutton, black, maintained

HALT/STOP-Button, Product range: RMQ16, Single unit, Design: Mushroom-shaped, Diameter: 28 mm, Illumination: Non-illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850, EN 418, Pushbutton remains in pushed position, Color Mushroom head: Black, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 × 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Emergency stop/emergency switching off pushbutton Catalog Number 257063 Model Code Q25PV-S EAN 4015082570637 Product Length/Depth 85 mm Product Height 28 mm Product Width 28 mm Product Weight 0.024 kg Certifications CSA File No.: 46552

UL 508

CSA Class No.: 3211-03

CE

UL Category Control No.: NKCR

CSA

UL File No.: E29184

UL

CSA-C22.2 No. 14-05

IEC/EN 60947-5 Catalog Notes Pushbutton remains in pushed position Features & Functions

Bezel color Black Bezel material Other Design Mushroom-shaped Features Tamper-proof (according to ISO 13850, EN 418) Illumination Non-illuminated Unlocking method Pull-release General

Degree of protection IP65

NEMA 1 Opening diameter 16 mm Product category RMQ16 Size Front dimensions: 25 × 25 mm Suitable for Emergency stop Type Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Actuator

Actuator color Red Actuator diameter 28 mm Actuator function Switching function latching

Pull-to-release Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25PV-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.