

INDUSTRIAL COMPONENT DATA

M22-PV/K01 216515 Y7-216515 EATON ELECTRIC

Emergency-stop key-release mushroom, 1 N/C, front mount

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PV/K01



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PV/K01
Catalog number	Y7-216515
Category	Emergency stop complete
Minimum order	5 Pcs
Document ID	EO-920E1D9DD8
Generated	2026-08-04

Product Overview

Emergency-stop key-release mushroom, 1 N/C, front mount

M22-PV/K01

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Pull-to-release function, 1 NC, Red, yellow

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Complete unit, Design:

Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Pull-to-release function, Connection type: Screw connection, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.8, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Standards: IEC/EN 60947, VDE 066

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 216515

Model Code M22-PV/K01 EAN 4015082165154 Product Length/Depth 90 mm Product Height 38 mm Product Width 38 mm

Product Weight 0.052 kg Certifications CE

CSA File No.: 012528

IEC/EN 60947-5

CSA-C22.2 No. 14-05

UL

VDE 0660

CSA-C22.2 No. 94-91

IEC/EN 60947

UL Category Control No.: NKCR

CSA Class No.: 3211-03

UL 508

UL File No.: E29184

CSA

DNV

GL

LR Catalog Notes Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11 Features & Functions

Base color Yellow Design Mushroom-shaped

Classical Features Tamper-proof (according to ISO 13850, EN 418) Illumination Non-illuminated Unlocking method

Pull-release General

Degree of protection IP66

NEMA 4X, 13 Lifespan, mechanical 100,000 Operations Mounting method Built-in Opening diameter 22.5 mm Operating

frequency 600 Operations/h Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front

dimensions: 35 mm Type Controlled stop pushbutton/emergency-stop button Ambient conditions, mechanical

Mounting position As required Shock resistance 50 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical r...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PV/K01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.