

## INDUSTRIAL COMPONENT DATA

# M22-PV/K11 216516 Y7-216516 EATON ELECTRIC

## Emergency-stop key-release mushroom, 1N/O+1N/C, front mount

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PV/K11



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | EATON - MOELLER         |
| MPN / Reference | M22-PV/K11              |
| Catalog number  | Y7-216516               |
| Category        | Emergency stop complete |
| Minimum order   | 5 Pcs                   |
| Document ID     | EO-359C6EFB80           |
| Generated       | 2026-08-05              |

### Product Overview

Emergency-stop key-release mushroom, 1N/O+1N/C, front mount

M22-PV/K11

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Pull-to-release function, 1 NC, 1 N/O, Red, yellow

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Complete unit, Design:

Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Pull-to-release function, Connection type: Screw connection, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts N/O = Normally open: 1 N/O, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.8, Maximum travel: mm 5.7, Minimum force for positive opening: N 20, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20,

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 216516

Model Code M22-PV/K11 EAN 4015082165161 Product Length/Depth 90 mm Product Height 38 mm Product Width 38 mm

Product Weight 0.062 kg Certifications IEC/EN 60947-5

UL 508

UL File No.: E29184

UL

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

IEC/EN 60947

CSA

CSA Class No.: 3211-03

CSA-C22.2 No. 94-91

VDE 0660

CE

CSA File No.: 012528

DNV

GL

LR Catalog Notes Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11

ETIM for 216516 Low-voltage industrial controls and switchgear (EC002034)

Feature Name

Feature Value

Unlocking method (EF001403)

Pull-release

Number of contacts as normally closed contact (EF008255)

1

Number of contacts as normally open contact (EF008256)

1

Degree of protection (IP) (EF005474)

IP66

Degree of protection (NEMA) (EF011959)

4X, 13

Mounting method (EF000003)

Built-in

With lighting (EF003829)

No

Supply voltage lamp (EF006522)

0 V

Hole diameter (EF000079)

22.5 mm

Connection type auxiliary circuit (EF006820)

Screw connection

Diameter cap (EF001423)

38 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PV/K11 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.