

INDUSTRIAL COMPONENT DATA

M22-PV45P 152862 Y7-152862 EATON ELECTRIC

Emergency-stop/off pushbutton, D 45mm, pull release

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PV45P



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PV45P
Catalog number	Y7-152862
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-5999B429C4
Generated	2026-07-27

Product Overview

Emergency-stop/off pushbutton, D=45mm, pull release

M22-PV45P

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Palm-tree shape, 45 mm, Non-illuminated, Pull-to-release function, Red, yellow

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Palm-tree shape, Diameter: 45 mm, Illumination: Non-illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: no, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 152862

Model Code M22-PV45P EAN 4015081496402 Product Length/Depth 67 mm Product Height 45 mm Product Width 45 mm

Product Weight 0.043 kg Compliances CE Certifications VDE 0660

IEC/EN 60947

DNV

GL

LR Features & Functions

Bezel color Other Base color Yellow Bezel material Other Color Red Design Palm-tree shaped

Classical Features Tamper-proof (according to ISO 13850, EN 418) Illumination Non-illuminated RAL-number 3000

Unlocking method Pull-release General

Degree of protection NEMA 4X

IP66 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Operating frequency 600 Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Suitable for Emergency stop Type Controlled stop pushbutton/emergency-stop button Ambient conditions, mechanical

Mounting position As required Shock resistance 50 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT No Actuator

Actuating force 50 N Actuator color Red Actuator diameter 45 mm Actuator function Switching f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PV45P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.