

INDUSTRIAL COMPONENT DATA

M22-PVL60P 152861 Y7-152861 EATON ELECTRIC

Emergency-stop/off pushbutton, D 60mm, illuminated, pull release

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PVL60P



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PVL60P
Catalog number	Y7-152861
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-46A1592350
Generated	2026-08-03

Product Overview

Emergency-stop/off pushbutton, D=60mm, illuminated, pull release

M22-PVL60P

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Palm-tree shape, 60 mm, Illuminated with LED element, Pull-to-release function, Red, yellow

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Palm-tree shape, Diameter: 60 mm, Illumination: Illuminated with LED element, Pull-to-release function, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: no, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 152861

Model Code M22-PVL60P EAN 4015081496396 Product Length/Depth 67 mm Product Height 60 mm Product Width 60

mm Product Weight 0.051 kg Certifications VDE 0660

IEC/EN 60947

DNV

GL

LR Catalog Notes Max. Configuration: 4 x M22-(C)K01, ...10 or 2 x M22-(C)K02, ...20, ...11 and 1 x M22-(F)LED... - When using M22-PVL... with 1 x M22-K01SMC10 (single channel), article M22-XSMC (order no.: 173030) is required. Order this item separately.

ETIM for 152861 Low-voltage industrial controls and switchgear (EC001038)

Feature Name

Feature Value

Colour button (EF000190)

Red

Construction type lens (EF006253)

Round

Diameter cap (EF001423)

60 mm

Hole diameter (EF000079)

22.5 mm

Width opening (EF004565)

0 mm

Height opening (EF004778)

0 mm

Degree of protection (IP) (EF005474)

IP66

Degree of protection (NEMA) (EF011959)

4X

Type of button (EF001546)

High

Suitable for lighting (EF001142)

Yes

With lighting (EF003829)

No

Supply voltage lamp (EF006522)

0 V

Switching function latching (EF007447)

Yes

Spring-return (EF001407)

No

With front ring (EF006014)

No

Material front ring (EF005972)

Other

Colour front ring (EF002429)

Other

Suitable for emergency stop (EF001433)

Yes

Unlocking method (EF001403)

Pull-release

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PVL60P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.