

INDUSTRIAL COMPONENT DATA

M22-PVS 216879 Y7-216879 EATON ELECTRIC

Emergency-stop pushbutton, D 38mm, key unlocking, MS1

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PVS



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PVS
Catalog number	Y7-216879
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-919CF265DD
Generated	2026-08-01

Product Overview

Emergency-stop pushbutton, D=38mm, key unlocking, MS1

M22-PVS

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Key-release, Red, yellow, RAL 3000, Not suitable for master key systems

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Key-release, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, RAL 3000, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: no, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Information about equipment supplied: 1 key included as standard, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 216879

Model Code M22-PVS EAN 4015082168797 Product Length/Depth 93 mm Product Height 38 mm Product Width 38 mm

Product Weight 0.06 kg Compliances CE Marked Certifications EN 60947-5

IEC 60947-5

CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-05

UL 508

VDE

CSA File No.: 012528

CSA-C22.2 No. 94-91

VDE 0660

UL

CE

IEC/EN 60947

UL File No.: E29184

CSA Class No.: 3211-03

IEC/EN 60947-5

UL Category Control No.: NKCR

CSA

CSA-C22.2 No. 14-05

DNV

GL

LR Catalog Notes Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11

ETIM for 216879 Low-voltage industrial controls and switchgear (EC001038)

Feature Name

Feature Value

Colour button (EF000190)

Red

Construction type lens (EF006253)

Round

Diameter cap (EF001423)

38 mm

Hole diameter (EF000079)

22.5 mm

Width opening (EF004565)

0 mm

Height opening (EF004778)

0 mm

Degree of protection (IP) (EF005474)

IP67/IP69K

Degree of protection (NEMA) (EF011959)

4X, 13

Type of button (EF001546)

High

Suitable for lighting (EF001142)

No

With lighting (EF003829)

No

Supply voltage lamp (EF006522)

0 V

Switching function latching (EF007447)

Yes

Spring-return (EF001407)

No
With front ring (EF006014)
No
Material front ring (EF005972)
Other
Colour front ring (EF002429)
Other
Suitable for emergency stop (EF001433)
Yes
Unlocking method (EF001403)
Key-release

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.