

INDUSTRIAL COMPONENT DATA

M22-PVS-MS2 111771 Y7-111771 EATON ELECTRIC Emergency-stop pushbutton, D 38mm, key unlocking, MS2

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PVS-MS2



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PVS-MS2
Catalog number	Y7-111771
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-8EA336F445
Generated	2026-08-03

Product Overview

Emergency-stop pushbutton, D=38mm, key unlocking, MS2

M22-PVS-MS2

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, MS2, Red

New product improvement: Improved gripability from lateral ribbed effect on the key. The key fulfills protection types IP66 and IP69K and is approved for worldwide use. The modular RMQ-Titan product range contains a wide variety of models relative to the emergency stop and emergency shutdown pushbutton. There are front elements in various forms, with and without illumination, pull or rotate released with and without key.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 111771
Model Code M22-PVS-MS2 EAN 4015081113217 Product Length/Depth 93 mm Product Height 38 mm Product Width 38 mm Product Weight 0.06 kg Certifications DNV

GL

LR Features & Functions

Bezel color Other Bezel material Other Design Palm-tree shaped Illumination Non-illuminated RAL-number 3000 Unlocking method Key-release General

Degree of protection IP67/IP69K

NEMA 4X Opening diameter 22.5 mm Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Suitable for Emergency stop Type Controlled stop pushbutton/emergency-stop button Ambient conditions, mechanical Mounting position As required Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Communication Connection to SmartWire-DT No Actuator Actuator color Red Actuator function Switching function latching Contacts Force for positive opening - min 0 N Design verification Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdiss 0 W Heat dissipation per pole, current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) 0 A Static heat dissipation, non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PVS-MS2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.