

INDUSTRIAL COMPONENT DATA

Q25LPV 072371 Y7-72371 EATON ELECTRIC Emergency-stop pushbutton, illuminated

Brand: EATON - MOELLER | Manufacturer Part Number: Q25LPV



Manufacturer	EATON - MOELLER
MPN / Reference	Q25LPV
Catalog number	Y7-72371
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-3A682776CE
Generated	2026-08-01

Product Overview

Emergency-stop pushbutton, illuminated

Emergency Stop Button 16 mm 25x25 mm Unlocking by

Eaton Moeller® series RMQ16 Emergency-stop pushbutton, illuminated

Emergency stop/emergency switching off pushbutton, Product range: RMQ16, Single unit, Design: Mushroom-shaped, Diameter: 28 mm, Illumination: Illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850, EN 418, Pushbutton remains in pushed position, I_e = 15 mA, Positive pole at X1, No bulb replacement required., Color Mushroom head: Red, Degree of Protection: IP65, Connection to SmartWire-DT: no, Front dimensions: 25 × 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Emergency stop/emergency switching off pushbutton Catalog Number 072371 Model Code Q25LPV EAN 4015080723714 Product Length/Depth 85 mm Product Height 28 mm Product Width 28 mm Product Weight 0.033 kg Certifications CSA Class No.: 3211-03

IEC/EN 60947

CSA-C22.2 No. 14-05

IEC/EN 60947-5

CSA

UL Category Control No.: NKCR

CE

CSA File No.: 46552

UL File No.: E29184

UL

UL 508 Features & Functions

Bezel color Other Bezel material Other Design Mushroom-shaped Features Tamper-proof (according to ISO 13850, EN 418) Illumination Illuminated Unlocking method Pull-release General

Degree of protection IP65

NEMA 1 Lifespan, mechanical 100,000 Operations Opening diameter 16 mm Operating frequency 600 Operations/h

Overvoltage category III Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage (Uimp) 800 V AC

Size Front dimensions: 25 × 25 mm Suitable for Illumination

Emergency stop Terminal capacity 0.5 - 1.0 mm² Terminal size 2.8 x 0.8 mm to DIN 46244, Blade terminal

2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors Type Controlled stop pushbutton/emergency-stop button

Ambient conditions, mechanical

Mounting position As required Shock resistance 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating tempe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q25LPV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.