

INDUSTRIAL COMPONENT DATA

M22-PVL 216878 Y7-216878 EATON ELECTRIC

Emergency-stop pushbutton, illuminated

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PVL



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PVL
Catalog number	Y7-216878
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-A4C3B4A738
Generated	2026-08-01

Product Overview

Emergency-stop pushbutton, illuminated

M22-PVL

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Illuminated with LED element, Pull-to-release function, Red, yellow, RAL 3000

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Illuminated with LED element, Pull-to-release function, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, RAL 3000, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: no, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 216878

Model Code M22-PVL EAN 4015082168780 Product Length/Depth 38 mm Product Height 70 mm Product Width 38 mm

Product Weight 0.039 kg Compliances CE Marked Certifications CSA Std. C22.2 No. 14-05

UL 508

CSA Std. C22.2 No. 94-91

EN 60947-5

IEC 60947-5

VDE

UL

IEC/EN 60947

UL Category Control No.: NKCR

CSA

IEC/EN 60947-5

UL File No.: E29184

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

VDE 0660

CE

CSA File No.: 012528

DNV

GL

LR Catalog Notes Max. Configuration: 4 x M22-(C)K01, ...10 or 2 x M22-(C)K02, ...20, ...11 and 1 x M22-(F)LED... - When using M22-PVL... with 1 x M22-K01SMC10 (single channel), article M22-XSMC (order no.: 173030) is required. Order this item separately.

ETIM for 216878 Low-voltage industrial controls and switchgear (EC001038)

Feature Name

Feature Value

Colour button (EF000190)

Red

Construction type lens (EF006253)

Round

Diameter cap (EF001423)

38 mm

Hole diameter (EF000079)

22.5 mm

Width opening (EF004565)

0 mm

Height opening (EF004778)

0 mm

Degree of protection (IP) (EF005474)

IP66

Degree of protection (NEMA) (EF011959)

4X, 13

Type of button (EF001546)

High

Suitable for lighting (EF001142)

Yes

With lighting (EF003829)

No

Supply voltage lamp (EF006522)

0 V

Switching function latching (EF007447)

Yes

Spring-return (EF001407)

No

With front ring (EF006014)

No

Material front ring (EF005972)

Other

Colour front ring (EF002429)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PVL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.