

## INDUSTRIAL COMPONENT DATA

# M22S-PVL 230962 Y7-230962 EATON ELECTRIC

## Emergency-stop pushbutton, illuminated

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-PVL



|                 |                                        |
|-----------------|----------------------------------------|
| Manufacturer    | EATON - MOELLER                        |
| MPN / Reference | M22S-PVL                               |
| Catalog number  | Y7-230962                              |
| Category        | Front element for mushroom push-button |
| Minimum order   | 1 Pcs                                  |
| Document ID     | EO-04995ED756                          |
| Generated       | 2026-08-01                             |

### Product Overview

Emergency-stop pushbutton, illuminated

M22S-PVL

Eaton Moeller® series M22 HALT/STOP-Button, RMQ-Titan, Mushroom-shaped, 38 mm, Illuminated with LED element, Pull-to-release function, Black, yellow, RAL 9005

HALT/STOP-Button, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Illuminated with LED element, Pull-to-release function, Color Mushroom head: Black, Color Base: yellow, Color RAL Value: RAL 9005, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 35, Standards: IEC/EN 60947, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 230962

Model Code M22S-PVL EAN 4015082309626 Product Length/Depth 38 mm Product Height 70 mm Product Width 38 mm

Product Weight 0.039 kg Certifications UL 508

CSA Class No.: 3211-03

UL Category Control No.: NKCR

CSA-C22.2 No. 94-91

UL

CE

CSA

CSA-C22.2 No. 14-05

IEC/EN 60947

IEC/EN 60947-5

CSA File No.: 012528

UL File No.: E29184

VDE 0660

DNV

GL

LR Catalog Notes Max. Configuration: 4 x M22-(C)K01, ...10 or 2 x M22-(C)K02, ...20, ...11 and 1 x M22-(F)LED... - When using M22-PVL... with 1 x M22-K01SMC10 (single channel), article M22-XSMC (order no.: 173030) is required. Order this item separately. Features & Functions

Bezel color Other Base color Yellow Bezel material Other Color Black Design Mushroom-shaped

Classical Illumination Illuminated with LED element RAL-number 9005 Unlocking method Pull-release General

Degree of protection IP67/IP69K

NEMA 4X, 13 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Operating frequency 600 Operations/h

Product category RMQ-Titan Size Front dimensions: 35 mm Suitable for Illumination Type Ambient conditions, mechanical

Mounting position As required Shock resistance 50 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proo...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-PVL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.