

INDUSTRIAL COMPONENT DATA

M22-PV 216876 Y7-216876 EATON ELECTRIC Emergency-stop pushbutton, non-illuminated

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PV



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PV
Catalog number	Y7-216876
Category	Front element for mushroom push-button
Minimum order	5 Pcs
Document ID	EO-82C1949C98
Generated	2026-08-03

Product Overview

Emergency-stop pushbutton, non-illuminated

M22-PV

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Pull-to-release function, Red, yellow, RAL 3000

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Pull-to-release function, Description: Tamper-proof according to ISO 13850/EN 418, Color Mushroom head: Red, Color Base: yellow, RAL 3000, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: no, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 emergency stop/emergency switching off pushbutton

Catalog Number 216876

Model Code M22-PV

EAN 4015082168766

Product Length/Depth 38 mm

Product Height 70 mm

Product Width 38 mm

Product Weight 0.039 kg

Compliances CE Marked

Certifications EN 60947-5

CSA Std. C22.2 No. 94-91

IEC 60947-5

UL 508

CSA Std. C22.2 No. 14-05

VDE

UL

CE

CSA File No.: 012528

IEC/EN 60947-5

CSA

IEC/EN 60947

UL File No.: E29184

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

VDE 0660

UL Category Control No.: NKCR

DNV

GL

LR

Catalog Notes Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11

Product specifications

Type Controlled stop pushbutton/emergency-stop button

Actuator color Red

Features Tamper-proof (according to ISO 13850, EN 418)

Actuator function Pull-to-release

Switching function latching

10.10 Temperature rise Not applicable.

10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements.

10.2.3.2 Verification of resis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.