

INDUSTRIAL COMPONENT DATA

M22S-PV 225528 Y7-225528 EATON ELECTRIC

Emergency-stop pushbutton, non-illuminated

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-PV



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-PV
Catalog number	Y7-225528
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-9BB26B6331
Generated	2026-08-03

Product Overview

Emergency-stop pushbutton, non-illuminated

M22S-PV

Eaton Moeller® series M22 HALT/STOP-Button, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Pull-to-release function, Black, yellow, RAL 9005

HALT/STOP-Button, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Pull-to-release function, Color Mushroom head: Black, Color Base: yellow, Color RAL Value: RAL 9005, Degree of Protection: IP66, IP69K, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 35, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 225528

Model Code M22S-PV EAN 4015082255282 Product Length/Depth 38 mm Product Height 70 mm Product Width 38 mm

Product Weight 0.039 kg Compliances CE Marked Certifications CSA Std. C22.2 No. 14-05

IEC 60947-5

EN 60947-5

CSA Std. C22.2 No. 94-91

UL 508

VDE
VDE 0660
IEC/EN 60947
IEC/EN 60947-5
CSA Class No.: 3211-03
UL
UL File No.: E29184
CE
CSA File No.: 012528
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94-91
UL Category Control No.: NKCR
CSA
DNV
GL
LR
ETIM for 225528 Low-voltage industrial controls and switchgear (EC001038)
Feature Name
Feature Value
Colour button (EF000190)
Black
Construction type lens (EF006253)
Round
Diameter cap (EF001423)
38 mm
Hole diameter (EF000079)
22.5 mm
Width opening (EF004565)
0 mm
Height opening (EF004778)
0 mm
Degree of protection (IP) (EF005474)
IP66
Degree of protection (NEMA) (EF011959)
4X, 13
Type of button (EF001546)
High
Suitable for lighting (EF001142)
No
With lighting (EF003829)
No
Supply voltage lamp (EF006522)
0 V
Switching function latching (EF007447)
No
Spring-return (EF001407)
No

With front ring (EF006014)

No

Material front ring (EF005972)

Other

Colour front ring (EF002429)

Other

Suitable for emergency stop (EF001433)

No

Unlocking method (EF001403)

Pull-release

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-PV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.