

INDUSTRIAL COMPONENT DATA

M22-PVS-MS* 216880 Y7-216880 EATON ELECTRIC Industrial Automation Bussines and Industrial Control Devices IE..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PVS-MS*



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PVS-MS*
Catalog number	Y7-216880
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-7F9E69B7ED
Generated	2026-08-02

Product Overview

Industrial Automation Bussines and Industrial Control Devices IEC - Pushbuttons

M22-PVS-MS*

Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton, RMQ-Titan, Mushroom-shaped, 38 mm, Non-illuminated, Key-release, selectable, Red, yellow, RAL 3000, Not suitable for master key systems

Emergency stop/emergency switching off pushbutton, Product range: RMQ-Titan, Single unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Key-release, Description: Tamper-proof according to ISO 13850/EN 418, Lock mechanism: selectable, Color Mushroom head: Red, Color Base: yellow, RAL 3000, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: no, Front dimensions: 35, Instructions: Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11, Information about equipment supplied: 1 key included as standard, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Emergency stop/emergency switching off pushbutton Catalog Number 216880

Model Code M22-PVS-MS* Product Length/Depth 93 mm Product Height 38 mm Product Width 38 mm Product Weight

0.06 kg Certifications CSA File No.: 012528

CE

UL Category Control No.: NKCR

VDE 0660

CSA-C22.2 No. 94-91

CSA-C22.2 No. 14-05

CSA

IEC/EN 60947

UL

UL 508

IEC/EN 60947-5

UL File No.: E29184

CSA Class No.: 3211-03

DNV

GL

LR Catalog Notes Max. number of contacts: four M22-(C)K01, ...10 or two M22-(C)K02, ...20, ...11

ETIM for 216880 Low-voltage industrial controls and switchgear (EC001038)

Feature Name

Feature Value

Colour button (EF000190)

Red

Construction type lens (EF006253)

Round

Diameter cap (EF001423)

38 mm

Hole diameter (EF000079)

22.5 mm

Width opening (EF004565)

0 mm

Height opening (EF004778)

0 mm

Degree of protection (IP) (EF005474)

IP67/IP69K

Degree of protection (NEMA) (EF011959)

4X, 13

Type of button (EF001546)

High

Suitable for lighting (EF001142)

No

With lighting (EF003829)

No

Supply voltage lamp (EF006522)

0 V

Switching function latching (EF007447)

Yes

Spring-return (EF001407)

No

With front ring (EF006014)

No

Material front ring (EF005972)

Other

Colour front ring (EF002429)

Other

Suitable for emergency stop (EF001433)

Yes

Unlocking method (EF001403)

Key-release

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PVS-MS* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.