

INDUSTRIAL COMPONENT DATA

M22-PVS/KC11/IY 216523 Y7-216523 EATON ELECTRIC

Emergency switching off key-operated button, 1N/O+1N/C, surf..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-PVS/KC11/IY



Manufacturer	EATON - MOELLER
MPN / Reference	M22-PVS/KC11/IY
Catalog number	Y7-216523
Category	Control circuit devices combination in enclosure
Minimum order	1 Pcs
Document ID	EO-A9D987E28C
Generated	2026-08-05

Product Overview

Emergency switching off key-operated button, 1N/O+1N/C, surface mounting

M22-PVS/KC11/IY

Eaton Moeller® series M22 Housing, Controlled stop pushbuttons/emergency-stop buttons, Mushroom-shaped, 38 mm, Non-illuminated, Key-release, 1 NC, 1 N/O, Screw connection, Number of locations 1, Red, Yellow Housing, Product range: RMQ-Titan, Complete unit, Design: Mushroom-shaped, Diameter: 38 mm, Non-illuminated, Key-release, Connection type: Screw connection, Description: Tamper-proof according to ISO 13850/EN 418, Number of locations: 1 Qty., Color Mushroom head: Red, Color Enclosure covers: Yellow, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts N/O = Normally open: 1 N/O, Contacts Notes = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.8, Maximum travel: mm 5.7, Minimum force for positive opening: N 20, Positive opening (ZW): yes, Front dimensions: 35, Information about equipment supplied: 1 key included as standard, Standards: IEC/EN 60947, VDE 0660, Mounting position: As required

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Housing Catalog Number 216523 Model Code M22-PVS/KC11/IY EAN

4015082165239 Product Length/Depth 115 mm Product Height 80 mm Product Width 72 mm Product Weight 0.214 kg

Certifications CE

CSA

CSA File No.: 012528

CSA-C22.2 No. 94-91

IEC/EN 60947-5

UL 508

CSA-C22.2 No. 14-05

UL File No.: E29184

IEC/EN 60947

UL Category Control No.: NKCR

CSA Class No.: 3211-03

UL

VDE 0660

ETIM for 216523 Low-voltage industrial controls and switchgear (EC000225)

Feature Name

Feature Value

Number of command positions (EF001372)

1

Number of push buttons (EF005558)

0

Number of indicator lights (EF001965)

0

Number of key switches (EF005590)

0

Number of selector switches (EF005567)

0

Number of mushroom-shaped push-buttons (EF006670)

1

Suitable for emergency stop (EF001433)

Yes

Rated control supply voltage AC 50 Hz (EF003978)

115 V

Rated control supply voltage AC 60 Hz (EF003979)

115 V

Rated control supply voltage DC (EF003980)

24 V

Colour housing cover (EF001373)

Yellow

Housing colour (EF000136)

Yellow

Housing material (EF001596)

Plastic

Number of contacts as normally open contact (EF008256)

1

Number of contacts as normally closed contact (EF008255)

1

Number of contacts as change-over contact (EF008257)

0

Degree of protection (IP) (EF005474)

IP67/IP69K

Degree of protection (NEMA) (EF011959)

4X, 13

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-PVS/KC11/IY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.