

INDUSTRIAL COMPONENT DATA

P1-25/XZ 046303 Y7-46303 EATON ELECTRIC Emergency switching off switch, 3p, 25A, replacement switch

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/XZ
Catalog number	Y7-46303
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D2CA651A9B
Generated	2026-08-05

Product Overview

Emergency switching off switch, 3p, 25A, replacement switch
ON-OFF 3-pole disconnect switch 25 A Replacement switch
25 A, Basic switch
On-Off switch, Design: Basic switch, Rated uninterrupted current: I_u = 25 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 046303 Model Code P1-25/XZ EAN 4015080463030

Product Length/Depth 131 mm Product Height 70 mm Product Width 49 mm Product Weight 0.131 kg Certifications CE

ETIM for 046303 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
25 A
Rated permanent current at AC-23, 400 V (EF011777)
25 A
Rated permanent current at AC-21, 400 V (EF009165)
25 A
Rated operation power at AC-3, 400 V (EF001364)
7.5 kW
Rated short-time withstand current Icw (EF007050)
0.64 kA
Rated operation power at AC-23, 400 V (EF007027)
13 kW
Switching power at 400 V (EF009166)
13 kW
Conditioned rated short-circuit current Iq (EF001444)
80 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Motor drive optional (EF007386)
No
Motor drive integrated (EF006697)
No
Voltage release optional (EF007491)
No
Device construction (EF008240)
Built-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.