

INDUSTRIAL COMPONENT DATA

EMIB00 EPDU MI 0U (309 16A 3P)36xC13:6xC19 EATON ELECTRIC Eaton Metered Input rack PDU, 0U, 42U, Input IEC-6..

Brand: EATON - MOELLER | Manufacturer Part Number: EMIB00



Manufacturer	EATON - MOELLER
MPN / Reference	EMIB00
Catalog number	EPDU MI 0U (309 16A 3P)36xC13:6xC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-01E45BAD16
Generated	2026-08-06

Product Overview

Eaton Metered Input rack PDU, 0U, 42U, Input IEC-60309 16A 3ph, 11 kW max, 16A, 346-415V, Outlets 36XC13 : 6XC19
EPDU MI 0U (309 16A 3P)36XC13:6XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton Metered Input rack PDU, 0U, 42U, Input IEC-60309 16A 3ph, 11 kW max, 16A, 346-415V, Outlets 36XC13 : 6XC19
Eaton Metered Input rack PDU, 0U, 42U, Input IEC-60309 16A 3ph, 11 kW max, 16A, 346-415V, Outlets 36XC13 : 6XC19
Phase Metering, Circuit Breaker Current Metering and Input Metering.
Hot-Swap Control module with advanced LCD.
Optional Temperature/Humidity sensor.
Built-in IEC outlet eGrip retention, retains all standard IEC plugs.
Daisy-Chain up to 8 ePDUs, reduce network infrastructure costs.
Power chain monitoring & Real time Intelligence on your Data Center, via Eaton Intelligent Power Manager Infrastructure.
Trigger advanced actions including VMware SRM and VM migration via Intelligent Power Manager IT software.
60°C Operating temperature.
Colour-coded outlet and branch circuits for simple load balancing.
Hydraulic-Magnetic Circuit Breakers with accidental trip protection.

Delivery program

ePDU General Prod Spec1Fitted With:Display

Mounting material

Ampere MeterTypeRack PDUIInput ConnectionIEC-60309 16A 3phCord Length3mInput

Voltage346-415VPhaseThree-phaseFrequency Rating50/60 HzEthernet InterfaceYesSerial InterfaceYesForm Factor0U
(Vertical)Outlet ControlNoOperating Temperature0° to 60°C (32° to 140°F)Outlets36XC13 : 6XC19Number of Outputs
C1336Number of Outputs C196Amperage Rating16AMounting DirectionVerticalETIM ClassEC002762ePDU Other Prod
SpecElectrical ConnectionConnecting cord with plugEvaluationAt distanceMounting Dimension (metrical)52Mounting
Dimension (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMIB00 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.