

INDUSTRIAL COMPONENT DATA

EMIB07 EPDU MI 0U (309 32A 3P)6xC13:12xC19 EATON ELECTRIC Eaton Metered Input rack PDU, 0U, 36U, Input IEC-6..

Brand: EATON - MOELLER | Manufacturer Part Number: EMIB07



Manufacturer	EATON - MOELLER
MPN / Reference	EMIB07
Catalog number	EPDU MI 0U (309 32A 3P)6xC13:12xC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-8D91E17995
Generated	2026-08-04

Product Overview

Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 6XC13 : 12XC19 EPDU MI 0U (309 32A 3P)6XC13:12XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 6XC13 : 12XC19 Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 6XC13 : 12XC19 Allows phase branch level metering for load balancing
 IEC outlet eGrip plug retention: retains all standard IEC plugs
 Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit
 Colour-coded outlet and branch circuits for simple load balancing
 Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection
 Low-profile form factor: 52mm wide x 53mm deep on most models
 60 Degree C operating temperature
 Optional Temp/Humidity sensor
 En masse configuration and update available via Intelligent Power Manager software
 Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software

Trigger advanced actions including VMware SRM and VM migration via Intelligent Power Manager software

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Installation: Button mounting on rear & side + variable mounting system

Delivery program

Type Rack PDU Input Connection IEC-60309 32A 3Ph Cord Length 3m Input Voltage 346-415V Phase Three-phase Frequency Rating 50/60 Hz Ethernet Interface Yes Serial Interface Yes Form Factor 0U (Vertical) Outlet Control No Operating Temperature 0° to 60°C (32° to 140°F) Outlets 6XC13 : 12XC19 Number of Outputs C136 Number of Outputs C1912 Amperage Rating 32A Mounting...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMIB07 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.