

## INDUSTRIAL COMPONENT DATA

# EMIB07 EPDU MI 0U (309 32A 3P)6xC13:12xC19 EATON ELECTRIC Eaton Metered Input rack PDU, 0U, 36U, Input IEC-6..

Brand: EATON - MOELLER | Manufacturer Part Number: EMIB07



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | EMIB07                              |
| Catalog number  | EPDU MI 0U (309 32A 3P)6xC13:12xC19 |
| Category        | Power distribution unit (PDU)       |
| Minimum order   | 1 Pcs                               |
| Document ID     | EO-8D91E17995                       |
| Generated       | 2026-08-05                          |

## Product Overview

Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 6XC13 : 12XC19  
EPDU MI 0U (309 32A 3P)6XC13:12XC19

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                |
|--------------|------------------------------------------------|
| Catalog path | EATON - MOELLER > Single-phase UPS up to 11kVA |
|--------------|------------------------------------------------|

## Additional Product Information

Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 6XC13 : 12XC19  
Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 6XC13 : 12XC19  
Allows phase branch level metering for load balancing  
IEC outlet eGrip plug retention: retains all standard IEC plugs  
Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit  
Colour-coded outlet and branch circuits for simple load balancing  
Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection  
Low-profile form factor: 52mm wide x 53mm deep on most models  
60 Degree C operating temperature  
Optional Temp/Humidity sensor  
En masse configuration and update available via Intelligent Power Manager software  
Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software

Trigger advanced actions including VMware SRM and VM migration via via Intelligent Power Manager software

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Installation: Button mounting on rear & side + variable mounting system

Delivery program

Type Rack PDU Input Connection IEC-60309 32A 3Ph Cord Length 3m Input Voltage 346-415V Phase Three-phase Frequency Rating 50/60 Hz Ethernet Interface Yes Serial Interface Yes Form Factor 0U (Vertical) Outlet Control No Operating Temperature 0° to 60°C (32° to 140°F) Outlets 6XC13 : 12XC19 Number of Outputs C136 Number of Outputs C1912 Amperage Rating 32A Mounting...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMIB07 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.