

INDUSTRIAL COMPONENT DATA

EMIB10 EATON ELECTRIC Eaton Metered Input rack PDU, 0U, 24U, Input IEC-60309 16A 1Ph, 3.7 kW max, 16A, 200-2..

Brand: EATON - MOELLER | Manufacturer Part Number: EMIB10



Manufacturer	EATON - MOELLER
MPN / Reference	EMIB10
Catalog number	10000
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-3C152CFD3D
Generated	2026-08-05

Product Overview

Eaton Metered Input rack PDU, 0U, 24U, Input IEC-60309 16A 1Ph, 3.7 kW max, 16A, 200-240V, Outlets 18XC13 : 2XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

Eaton Metered Input rack PDU, 0U, 24U, Input IEC-60309 16A 1Ph, 3.7 kW max, 16A, 200-240V, Outlets 18XC13 : 2XC19

Eaton Metered Input rack PDU, 0U, 24U, Input IEC-60309 16A 1Ph, 3.7 kW max, 16A, 200-240V, Outlets 18XC13 : 2XC19

Allows phase branch level metering for load balancing

IEC outlet eGrip plug retention: retains all standard IEC plugs

Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit

Colour-coded outlet and branch circuits for simple load balancing

Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52mm wide x 53mm deep on most models

60 Degree C operating temperature

Optional Temp/Humidity sensor

En masse configuration and update available via Intelligent Power Manager software

Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software

Trigger advanced actions including Vmware SRM and VM migration via via Intelligent Power Manager software

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Installation: Button mounting on rear & side + variable mounting system

[Delivery program

Power Distribution Prod Spec Type Rack PDU ePDU Other Prod Spec Electrical Connection Connecting cord with plug
Evaluation At distance Mounting Dimension (metrical) 52 Mounting Dimension (standardised) Metric Ampere Meter Yes
Switchable No Over Voltage Category 2 ePDU Input Prod Spec Input Connection IEC-60309 16A 1Ph Cord Length...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMIB10 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.