

INDUSTRIAL COMPONENT DATA

EMIB22 EPDU MI 0U (C20 16A 1P)20XC13:4XC19 EATON ELECTRIC Eaton Metered Input rack PDU, 0U, 24U, Input C20,

..

Brand: EATON - MOELLER | Manufacturer Part Number: EMIB22



Manufacturer	EATON - MOELLER
MPN / Reference	EMIB22
Catalog number	EPDU MI 0U (C20 16A 1P)20XC13:4XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-CDB6D3F1EA
Generated	2026-08-04

Product Overview

Eaton Metered Input rack PDU, 0U, 24U, Input C20, 3.7 kW max, 16A, 200-240V, Outlets 20XC13:4XC19
EPDU MI 0U (C20 16A 1P)20XC13:4XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton Metered Input rack PDU, 0U, 24U, Input C20, 3.7 kW max, 16A, 200-240V, Outlets 20XC13:4XC19
Eaton Metered Input rack PDU, 0U, 24U, Input C20, 3.7 kW max, 16A, 200-240V, Outlets 20XC13:4XC19
Allows phase branch level metering for load balancing

IEC outlet eGrip plug retention: retains all standard IEC plugs

Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit

Colour-coded outlet and branch circuits for simple load balancing

Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52mm wide x 53mm deep on most models

60 Degree C operating temperature

Optional Temp/Humidity sensor

En masse configuration and update available via Intelligent Power Manager software

Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software

Trigger advanced actions including VMware SRM and VM migration via Intelligent Power Manager software

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Installation: Button mounting on rear & side + variable mounting system

Delivery program

Type Rack PDU Input Connection C20 Cord Length 3m Input Voltage 200-240V Phase Single-phase Frequency Rating 50/60 Hz Ethernet Interface Yes Serial Interface Yes Form Factor 0U (Vertical) Outlet Control No Operating Temperature 0° to 60°C (32° to 140°F) Outlets 20XC13:4XC19 Number of Outputs C13 20 Number of Outputs C19 4 Amperage Rating 16A Mounting Direction Vertical ETIM Class EC002762e PDU Gene...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMIB22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.