

INDUSTRIAL COMPONENT DATA

EMIB22 EPDU MI 0U (C20 16A 1P)20XC13:4XC19 EATON ELECTRIC Eaton Metered Input rack PDU, 0U, 24U, Input C20,

..

Brand: EATON - MOELLER | Manufacturer Part Number: EMIB22



Manufacturer	EATON - MOELLER
MPN / Reference	EMIB22
Catalog number	EPDU MI 0U (C20 16A 1P)20XC13:4XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-CDB6D3F1EA
Generated	2026-08-05

Product Overview

Eaton Metered Input rack PDU, 0U, 24U, Input C20, 3.7 kW max, 16A, 200-240V, Outlets 20XC13:4XC19
EPDU MI 0U (C20 16A 1P)20XC13:4XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton Metered Input rack PDU, 0U, 24U, Input C20, 3.7 kW max, 16A, 200-240V, Outlets 20XC13:4XC19
Eaton Metered Input rack PDU, 0U, 24U, Input C20, 3.7 kW max, 16A, 200-240V, Outlets 20XC13:4XC19
Allows phase branch level metering for load balancing

IEC outlet eGrip plug retention: retains all standard IEC plugs

Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit

Colour-coded outlet and branch circuits for simple load balancing

Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52mm wide x 53mm deep on most models

60 Degree C operating temperature

Optional Temp/Humidity sensor

En masse configuration and update available via Intelligent Power Manager software

Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software

Trigger advanced actions including VMware SRM and VM migration via via Intelligent Power Manager software

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Installation: Button mounting on rear & side + variable mounting system

Delivery program

TypeRack PDUInput ConnectionC20Cord Length3mInput Voltage200-240VPhaseSingle-phaseFrequency Rating50/60
HzEthernet InterfaceYesSerial InterfaceYesForm Factor0U (Vertical)Outlet ControlNoOperating Temperature0° to 60°C
(32° to 140°F)Outlets20XC13:4XC19Number of Outputs C1320Number of Outputs C194Amperage Rating16AMounting
DirectionVerticalETIM ClassEC002762ePDU Gene...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMIB22 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.