

INDUSTRIAL COMPONENT DATA

EMIB32 EPDU MI 0U (309 32A 3P)24XC13:6XC19 EATON ELECTRIC Eaton Metered Input rack PDU, 0U, 36U, Input IEC-6..

Brand: EATON - MOELLER | Manufacturer Part Number: EMIB32



Manufacturer	EATON - MOELLER
MPN / Reference	EMIB32
Catalog number	EPDU MI 0U (309 32A 3P)24XC13:6XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-3A160BFE0F
Generated	2026-08-05

Product Overview

Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 24XC13:6XC19 EPDU MI 0U (309 32A 3P)24XC13:6XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 24XC13:6XC19 Eaton Metered Input rack PDU, 0U, 36U, Input IEC-60309 32A 3Ph, 22 kW max, 32A, 346-415V, Outlets 24XC13:6XC19 Allows phase branch level metering for load balancing
IEC outlet eGrip plug retention: retains all standard IEC plugs
Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit
Colour-coded outlet and branch circuits for simple load balancing
Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection
Low-profile form factor: 52mm wide x 53mm deep on most models
60 Degree C operating temperature
Optional Temp/Humidity sensor
En masse configuration and update available via Intelligent Power Manager software
Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software

Trigger advanced actions including VMware SRM and VM migration via via Intelligent Power Manager software

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Installation: Button mounting on rear & side + variable mounting system

Delivery program

ePDU General Prod Spec1Fitted With:Ampere Meter

Mounting material

DisplayTypeRack PDUInput ConnectionIEC-60309 32A 3PhCord Length3mInput

Voltage346-415VPhaseThree-phaseFrequency Rating50/60 HzEthernet InterfaceYesSerial InterfaceYesForm Factor0U
(Vertical)Outlet ControlNoOperating Temperature0° to 60°C (32° to 140°F)Outlets24XC13:6XC19Numb...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMIB32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.