

INDUSTRIAL COMPONENT DATA

EMOB22 EPDU MO 0U (C20 16A 1P)20XC13:4XC19 EATON ELECTRIC Eaton Metered Outlet Rack PDU, 0U, 36U, Input C20,..

Brand: EATON - MOELLER | Manufacturer Part Number: EMOB22



Manufacturer	EATON - MOELLER
MPN / Reference	EMOB22
Catalog number	EPDU MO 0U (C20 16A 1P)20XC13:4XC19
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-628052558E
Generated	2026-08-05

Product Overview

Eaton Metered Outlet Rack PDU, 0U, 36U, Input C20, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19
EPDU MO 0U (C20 16A 1P)20XC13:4XC19

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

Eaton Metered Outlet Rack PDU, 0U, 36U, Input C20, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19
Eaton Metered Outlet Rack PDU, 0U, 36U, Input C20, 3.84 kW max, 16A, 200-240V, Outlets 20XC13 : 4XC19
Allows device level metering over A and B feeds (Requires Daisy Chained ePDUs)
Input and Phase Metering, Circuit Breaker Current Metering
Circuit Breaker status monitoring
Level 3 PUE measurements
Highly secure with user access control, password protection and SSL configurable to 1024 or 2048 bit
IEC outlet eGrip plug retention: retains all standard IEC plugs
60 Degree C operating temperature
Colour-coded outlet and branch circuits for simple load balancing
Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection
Low-profile form factor: 52mm wide x 53mm deep on most models

En masse configuration and update available via Intelligent Power Manager software

Single Pane Monitoring of many ePDUs+UPS as part of the power chain, via Intelligent Power Manager software

HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

Installation: Button mounting on rear & side + variable mounting system

Optional Temp/Humidity sensor

Delivery program

Type Rack PDU Input Connection C20 Cord Length 3m Input Voltage 200-240V Phase Single-phase Frequency Rating 50/60 Hz Ethernet Interface Yes Serial Interface Yes Form Factor 0U (Vertical) Outlet Control No Operating Temperature 0° to 60°C (32° to 140°F) Outlets 20XC13 : 4XC19 Number of Outputs C13 20 Number of Outputs C19 4 Amperage Rating 16A Mounti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMOB22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.