

INDUSTRIAL COMPONENT DATA

EMS-DOS-T-9-SWD 170111 EATON ELECTRIC Starter Direct 9 SWD With emergency stop

Brand: EATON - MOELLER | Manufacturer Part Number: EMS-DOS-T-9-SWD



Manufacturer	EATON - MOELLER
MPN / Reference	EMS-DOS-T-9-SWD
Catalog number	170111
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-2FEF84F42F
Generated	2026-08-05

Product Overview

Starter Direct 9; SWD; With emergency stop

Electronic starter; Direct start; 9 A; With SmartWire-DT; Emergency Stop

DOL starter, 24 V DC, 1,5 - 7 (AC-53a), 9 (AC-51) A, Push in terminals, SmartWire-DT slave, Controlled stop

DOL starter, Actuating voltage: 24 V DC, Standards: IEC/EN 60947-4-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Standard Soft Starters**

Additional Product Information

DOL starter, 24 V DC, 1,5 - 7 (AC-53a), 9 (AC-51) A, Push in terminals, SmartWire-DT slave, Controlled stopDOL starter, Actuating voltage: 24 V DC, Standards: IEC/EN 60947-4-2Delivery program

This item is only available for a limited time. Replacement item: Art. no. 192389, Type: EMS2-DOS-T-9-SWDProduct rangeElectronic motor starterProduct rangeSmartWire-DT slaveSubrangeSmartWire-DT electronic motor startersBasic functionDOL starters (complete devices)FunctionFor connecting to SmartWire-DT for expanded diagnostics.DescriptionDOL starting

Motor protection

Circuit design: safety output stage with bypass, three-phase disconnect.

Controlled stop via additional enable signal terminal up to SIL3/Plc.MessagesOperational readiness

Operating direction feedback

Enable signal

Motor current in %

Motor current in A
Thermal motor image in %
Overload prewarning
Trip indications (overload, phase failure, etc.)
Set short-circuit release value
Device TypeCommandsOperating the motor starter
Manual reset
Automatic resetMotor ratingsMax. rating for three-phase motors, 50 - 60 HzAC-53a380 V 400 V 415 V [P]0.55 - 3 kWSetting
range of overload releases[Ir]1,5 - 7 (AC-53a)
9 (AC-51) A_xActuating voltage24 V DCConnection techniquePush in terminalsStop FunctionControlled stopConnection to
SmartWire-DTyesTechnical data
GeneralStandardsIEC/EN 60947-4-2DimensionsWidth30 mmDimensionsHeight157 mmDimensionsDepth124
mmWeight0.3 kgMountingTop-hat rail IEC/EN 60715, 35 mmProtection type (IEC/EN 60529, EN50178,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMS-DOS-T-9-SWD with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.