


INDUSTRIAL COMPONENT DATA

EMS-XCW-3 172742 EATON ELECTRIC Connector with cable control 3 Devices

Brand: EATON - MOELLER | Manufacturer Part Number: EMS-XCW-3



Manufacturer	EATON - MOELLER
MPN / Reference	EMS-XCW-3
Catalog number	172742
Category	Accessories/spare parts for electronic motor control and protection
Minimum order	1 Pcs
Document ID	EO-D83A2B5973
Generated	2026-08-04

Product Overview

Connector with cable control; 3 Devices

Switching connection bridge for EMS; 3 devices

Control cable connector; 3 Devices

Prefabricated connection cable for wiring the control current for 3 electronic motor starters in parallel with a max. mounting distance of 30 mm, conductor cross-section: 0.75 mm².

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Standard Soft Starters

Additional Product Information

General specifications

Product Name Eaton Moeller® series EMS control cable connector Catalog Number 172742 Model Code EMS-XCW-3 EAN 4015081693009 Product Length/Depth 220 mm Product Height 150 mm Product Width 160 mm Product Weight 0.03 kg

Compliances CE Catalog Notes Conductor cross-section: 0.75 mm² Features & Functions

Number Of Poles Single-pole General

Accessory/spare part type Connecting cable Product category Used with 3 devices can be connected Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Design verification

Equipment heat dissipation, current-dependent Pvid 0.007 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole, current-dependent Pvid 0.007 W Rated operational current for specified heat dissipation (In) 0.4 A Static heat dissipation, non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical impact Does not apply...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMS-XCW-3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.