

INDUSTRIAL COMPONENT DATA

EMS2-ROS-T-9-SWD 192390 Y7-192390 EATON ELECTRIC Starter electronic Starter inverter 9-To With SmartWire-DT ..

Brand: EATON - MOELLER | Manufacturer Part Number: EMS2-ROS-T-9-SWD



Manufacturer	EATON - MOELLER
MPN / Reference	EMS2-ROS-T-9-SWD
Catalog number	Y7-192390
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-96E6BDF5B3
Generated	2026-08-06

Product Overview

Starter electronic; Starter inverter; 9-To; With SmartWire-DT; Emergency Stop; pressure Connection

EMS2-ROS-T-9-SWD

Reversing starter, 24 V DC, 1,5 - 7 (AC-53a), 9 (AC-51) A, Push in terminals, SmartWire-DT slave, Controlled stop, PTB 19 ATEX 3000

Reversing starter, Product range: Electronic motor starter, SmartWire-DT slave, Function: For connecting to SmartWire-DT for expanded diagnostics, Description: DOL starting, Reversing start, Motor protection, Circuit design: safety output stage with bypass, three-phase disconnect., Controlled stop via additional enable signal terminal up to SIL3/Plc., Conformity, Approval Explosion protection (according to ATEX 94/9/EC): II (2) G [Ex e] [Ex d] [Ex px], II (2) D [Ex t] [Ex p], Conformity, Approval EC-prototype test certification: PTB 13 ATEX 3003, Motor ratings Max. rating for three-phase motors , 50 - 60 Hz AC-53a 380 V 400 V 415 V: P= 0.55 - 3 kW, Setting range of overload releases: Ir= 1,5 - 9 A_x, Actuating voltage: 24 V DC, Connection technique: Push in terminals, Stop Function: Controlled stop, Connection to SmartWire-DT: yes, Mounting position: Vertical, Motor feeder at bottom, Standards: IEC/EN 60947-4-2, IEC 61508, ISO 13849, UL508

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Standard Soft Starters

Additional Product Information

Reversing starter, 24 V DC, 1,5 - 7 (AC-53a), 9 (AC-51) A, Push in terminals, SmartWire-DT slave, Controlled stop, PTB 19 ATEX 3000 Reversing starter, Product range: Electronic motor starter, SmartWire-DT slave, Function: For connecting to SmartWire-DT for expanded diagnostics, Description: DOL starting, Reversing start, Motor protection, Circuit design: safety output stage with bypass, three-phase disconnect., Controlled stop via additional enable signal terminal up to SIL3/Plc.,

Conformity, Approval Explosion protection (according to ATEX 94/9/EC): II (2) G [Ex e] [Ex d] [Ex px], II (2) D [Ex t] [Ex p],
Conformity, Approval EC-prototype test certification: PTB 13 ATEX 3003, Motor ratings Max. rating for three-phase motors,
50 - 60 Hz AC-53a 380 V 400 V 415 V: P= 0.55 - 3 kW, Setting range of overload releases: Ir= 1,5 - 9 A_x, Actuating
voltage: 24 V DC, Connection technique: Push in terminals, Stop Function: Controlled stop, Connection to SmartWire-DT:
yes, Mounting position: Vertical, Motor feeder at bottom, Standards: IEC/EN 60947-4-2, IEC 61508, ISO 13849,
UL508Delivery program
Product rangeElectronic motor starterProduct rangeSmartWire-DT slaveSubrangeSmartWire-DT electronic motor
startersBasic functionReversing starters (completeddevices)FunctionFor connecting to SmartWire-DT for expanded
diagnosticsDescriptionDOL starting
Reversing start
Motor protection
Circuit design: safety output stage with bypass, three-phase disconnect.
Controlled stop via additional enable sign...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMS2-ROS-T-9-SWD with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.