

INDUSTRIAL COMPONENT DATA

EMS2-ROSF-Z-3-24VDC 192399 Y7-192399 EATON ELECTRIC Starter electronic Starter inverter 3 A 24 V DC Emergenc..

Brand: EATON - MOELLER | Manufacturer Part Number: EMS2-ROSF-Z-3-24VDC



Manufacturer	EATON - MOELLER
MPN / Reference	EMS2-ROSF-Z-3-24VDC
Catalog number	Y7-192399
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-2FCF7351AB
Generated	2026-08-05

Product Overview

Starter electronic; Starter inverter; 3 A; 24 V DC; Emergency Stop; Fuses integrated; Connection-screw
EMS2-ROSF-Z-3-24VDC

Eaton Moeller® series EMS2 Reversing starter, 24 V DC, 0,18 - 3 A, Screw terminals, Controlled stop, PTB 19 ATEX 3000
EMS2-ROSF-Z-3-24VDC

Reversing starter, Product range: Electronic motor starter, Description: DOL starting, Reversing start, Motor protection, Circuit design: safety output stage with bypass, three-phase disconnect., Controlled stop via additional enable signal terminal up to SIL3/Plc., Conformity, Approval Explosion protection (according to ATEX 94/9/EC): II (2) G [Ex e] [Ex d] [Ex px], II (2) D [Ex t] [Ex p], Conformity, Approval EC-prototype test certification: PTB 13 ATEX 3003, Max. motor rating for three-phase motors, 50 - 60 Hz AC-53a 380 V 400 V 415 V: P= 0.06 - 0.75 kW, Setting range of overload releases: Ir= 0,18 - 3 A_x, Actuating voltage: 24 V DC, Connection technique: Screw terminals, Stop Function: Controlled stop, Connection to SmartWire-DT: no, Mounting position: Vertical, Motor feeder at bottom, Standards: IEC/EN 60947-4-2, IEC 61508, ISO 13849, UL508

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Standard Soft Starters
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series EMS2 Reversing starter Catalog Number 192399 Model Code

EMS2-ROSF-Z-3-24VDC EAN 4015081930968 Product Length/Depth 114.5 mm Product Height 160 mm Product Width 22.5 mm Product Weight 0.35 kg Certifications IEC 61508

UL508

IEC/EN 60947-4-2

EN ISO 13849

UL File No.: E29096

UL Category Control No.: NLDX, NLDX7

PTB 19 ATEX 3000

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CE marking

UL listed

Certified by UL for use in Canada

UL report applies to both US and Canada Features & Functions

Fitted with: fuse Functions Temperature compensated overload protection

DOL starting

Motor protection

Controlled stop

Reversing start General

Class CLASS 10 Connection to SmartWire-DT No Degree of protection IP20

NEMA Other Model Reversing starter Mounting method Mounting on Busbar 60 mm

Rail mounting possible

Motor starter Feeder System

Mounting on Busbar 30 mm

Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Mounting position Vertical

Motor feeder at bottom Overload release current setting - min 0.18 A Overload release current setting - max 3 A Product category Electronic motor starter Residual ripple $\leq 5\%$ (input voltage) Terminal capacity 0.2 - 2.5 mm², Main cables

0.14 - 2.5 mm², Control circuit cables Terminal capacity (AWG) 26 - 14, Control circuit cables

24 - 14, Main cables Type Reversing starter (complete device) Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating tempera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMS2-ROSF-Z-3-24VDC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.