

INDUSTRIAL COMPONENT DATA

EPDU SW 0U (C14 10A 1P)16XC13 ESWB03 EATON ELECTRIC

Eaton Switched Rack PDU, 0U, 26U, Inputs C14, 2.3 kW max..

Brand: EATON - MOELLER | Manufacturer Part Number: EPDU SW 0U (C14 10A 1P)16XC13



Manufacturer	EATON - MOELLER
MPN / Reference	EPDU SW 0U (C14 10A 1P)16XC13
Catalog number	ESWB03
Category	Power distribution unit (PDU)
Minimum order	1 Pcs
Document ID	EO-8D886C79B6
Generated	2026-08-03

Product Overview

Eaton Switched Rack PDU, 0U, 26U, Inputs C14, 2.3 kW max, 10A, 200-240V, Outlets 16XC13
EPDU SW 0U (C14 10A 1P)16XC13

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

Eaton Switched Rack PDU, 0U, 26U, Inputs C14, 2.3 kW max, 10A, 200-240V, Outlets 16XC13
Eaton Switched Rack PDU, 0U, 26U, Inputs C14, 2.3 kW max, 10A, 200-240V, Outlets 16XC13
Securely allows remote control and remote rebooting
Highly secure with Admin controlling user access permission, password protection and SSL configurable to 1024 or 2048 bit
Switch equipment on/off across both A and B feed (Requires Daisy Chained ePDUs)
Sequence outlets to avoid in-rush current, to ensure equipment starts in correct order
Input and Phase Metering, Circuit Breaker Current Metering
IEC outlet eGrip plug retention: retains all standard IEC plugs
60 Degree C operating temperature
Colour-coded outlet and branch circuits for simple load balancing
Eaton Hydraulic-Magnetic Circuit Breakers with accidental trip protection
Low-profile form factor: 52mm wide x 53mm deep on most models
En masse configuration and update available via Intelligent Power Manager software
Single Pane Monitoring of many ePDUs+UPS as part of the power chain, & graceful Equipment shut down via Intelligent Power Manager software

Installation: Button mounting on rear & side + variable mounting system

Delivery program

Type Rack PDU Input Connection C14 Cord Length 3m Input Voltage 200-240V Phase Single-phase Frequency Rating 50/60 Hz Ethernet Interface Yes Serial Interface Yes Form Factor 0U (Vertical) Outlet Control Yes Operating Temperature 0° to 60°C (32° to 140°F) Outlets 16XC13 Number of Outputs C13 16 Number of Outputs C19 0 Amperage Rating 10A Mount...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EPDU SW 0U (C14 10A 1P) 16XC13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.